



BN 75-01Y

- Long life
- Float switch
- with connector
- 1 Reed contacts
- Non-contact principle
- 80 mm x 99,5 mm x 55 mm
- Thermoplastic enclosure
- Available with M12 plug-in connector and pre-wired cable

Data

Ordering data

	BN 75-01Y
	101055740
EAN (European Article Number)	4030661009384
eCl@ss number, Version 9.0	27-27-01-05

General data

	BN 75
Active principle	Magnetic drive
Housing construction form	Special construction
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Plastic
Gross weight	80 g

General data - Features

Number of openers	1
-------------------	---

Mechanical data

Actuating element	Magnet
Mechanical life, minimum	1,000,000,000 Operations
Hysteresis (Switch distance), maximum	3 mm

Mechanical data - Connection technique

Terminal Connector	Connector
--------------------	-----------

Mechanical data - Dimensions

Height of sensor	99.5 mm
Length of sensor	55 mm
Width of sensor	80 mm

Ambient conditions

	IP65
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C

Electrical data

Voltage type	AC (alternating current)
Switching voltage, maximum	220 VAC
Switching current, maximum	1 A
Switching capacity, maximum	60 W
Switching capacity, maximum	60 VA
Switching element	Opener (NC)
Bounce duration, minimum	0.3 ms
Bounce duration, maximum	0.6 ms

Electrical data - Digital Output

Versions	Reed contacts
----------	---------------

Notes

Note (General)	Depending on how the floater is assembled, either a NO contact or a NC contact is possible. The indicated switching points are applicable for water
----------------	--

Pictures

Photo/Product/Catalogue




ID: kbn75f01

| 560,2 kB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 Pixel - 72 dpi

| 48,7 kB | .png | 74.083 x 111.125 mm - 210 x 315 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1bn75g01

| 24,8 kB | .cdr |

| 79,9 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693 Pixel - 72 dpi

| 4,0 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel - 72 dpi

Graphic/Product/Contact




ID: 1bn75k02

| 50,7 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693 Pixel - 72 dpi

| 22,4 kB | .cdr |

Diagramm/Product/Curve



ID: kbn32d01

| 110,5 kB | .jpg | 352.425 x 371.828 mm - 999 x 1054 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 412021-01-31T16:26:41+01:000401Europe/BerlinSun, 31 Jan 2021 16:26:41

+010041pmSunday.31pm31Europe/BerlinCET2601Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:26:41

+010001pm31