

## CSS 14-34F0-S-D-M-ST

- Actuation from side
- Thermoplastic enclosure
- 27 mm x 108.2 mm x 35 mm
- Misaligned actuation possible
- 1 x connector plug M12, 8-pole
- Electronic contact-free, coded system
- Max. length of the sensor chain 200 m
- 2 short-circuit proof PNP safety outputs
- High repeat accuracy of the switching points
- To control positive-guided relay without downstream safety monitoring module
- without edge monitoring of the enabling pushbutton, suitable for automatic start
- Integral cross-short, wire-breakage and external voltage monitoring of the safety cables up to the control cabinet
- Suitable as individual or terminal device in series-wiring of standards sensors to replace a safety monitoring module
- Self-monitored series-wiring of up to 30 CSS 34 sensors and one CSS 34F0/F1 sensor for control category 4 to ISO 13849-1



## Data

### Ordering data

CSS 14-34F0-S-D-M-ST  
101188767

|                               |               |
|-------------------------------|---------------|
| EAN (European Article Number) | 4030661354866 |
| eCl@ss number, Version 9.0    | 27-27-24-03   |

## Approval - Standards

TÜV  
cULus  
EAC

## General data

|                                      |                                       |
|--------------------------------------|---------------------------------------|
|                                      | CSS 34                                |
|                                      | IEC 60947-5-3                         |
| Active principle                     | inductive                             |
| Housing construction form            | Block                                 |
| Installation conditions (mechanical) | not flush                             |
| Sensor topology                      | Sensor for series wiring              |
| Enclosure material                   | Glass-fibre, reinforced thermoplastic |
| Active area                          | Glass-fibre, reinforced thermoplastic |
| Gross weight                         | 142 g                                 |
| Reaction time, maximum               | 30 ms                                 |
| Duration of risk, maximum            | 60 ms                                 |

## General data - Features

|                                                             |     |
|-------------------------------------------------------------|-----|
| Diagnostic output                                           | Yes |
| Short circuit detection                                     | Yes |
| Short-circuit recognition                                   | Yes |
| Safety functions                                            | Yes |
| Cascadable                                                  | Yes |
| Input for enabling pushbutton, suitable for automatic start | Yes |
| Integral System Diagnostics, status                         | Yes |
| Number of LEDs                                              | 3   |
| Number of semi-conductor outputs with signaling function    | 1   |
| Number of fail-safe digital outputs                         | 2   |
| Number of Series-wiring of sensors                          | 31  |

## Safety appraisal

|                                              |                                           |
|----------------------------------------------|-------------------------------------------|
|                                              | ISO 13849-1<br>IEC 60947-5-3<br>IEC 61508 |
| Performance level, up to                     | e                                         |
| Control category to EN13849                  | 4                                         |
| PFH-value                                    | $3.60 \times 10^{-9}$ /h                  |
| Safety Integrity Level (SIL), applicable for | 3                                         |
| Mission Time                                 | 20 Year(s)                                |

## Mechanical data

|                                        |                                                                                                                                                                     |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Actuating panels                       | lateral                                                                                                                                                             |
| Active area                            | lateral                                                                                                                                                             |
| Switch distance                        | 14 mm                                                                                                                                                               |
| Ensured switch distance "ON" $S_{ao}$  | 8 mm                                                                                                                                                                |
| Ensured switch distance "OFF" $S_{ar}$ | 17 mm                                                                                                                                                               |
| Actuator switch distance               | Actuator CST 180-1 / CST 180-2: 10 mm                                                                                                                               |
|                                        | Actuator CST 34-S-1: 14 mm                                                                                                                                          |
|                                        | Actuator CST 34-S-2: 14 mm                                                                                                                                          |
|                                        | Actuator CST 34-S-3: 14 mm                                                                                                                                          |
|                                        | Actuator CST 34-S-1: 12 mm                                                                                                                                          |
|                                        | Actuator CST 34-S-2: 12 mm                                                                                                                                          |
|                                        | Actuator CST 34-S-3: 12 mm                                                                                                                                          |
|                                        | Actuator CST 180-1 / CST 180-2: 8 mm                                                                                                                                |
|                                        | Actuator CST 34-S-1: 17 mm                                                                                                                                          |
|                                        | Actuator CST 34-S-2: 17 mm                                                                                                                                          |
|                                        | Actuator CST 34-S-3: 17 mm                                                                                                                                          |
|                                        | Actuator CST 180-1 / CST 180-2: 13 mm                                                                                                                               |
| Hysteresis (Switch distance), maximum  | 1.5 mm                                                                                                                                                              |
| Repeat accuracy R R                    | 0.5 mm                                                                                                                                                              |
| Note (Repeat accuracy $R$ )            | Axial offset: The long side allows for a maximum height misalignment (x) of sensor and actuator of 36 mm (e.g. mounting tolerance or due to guard door sagging).    |
|                                        | Increased misalignment, max. 53 mm, possible when the CST 34-S-2 actuator is used. The axial misalignment (y) is max. $\pm 10$ mm (see figure: Operating principle) |

## Mechanical data - Connection technique

|                    |                                                                                                                                                                                 |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Terminal Connector | Connector plug M12, 8-pole                                                                                                                                                      |
| Note               | The cable section of the interconnecting cable must be observed for both wiring variants! Cable length and cable section alter the voltage drop depending on the output current |

### Mechanical data - Dimensions

|                  |          |
|------------------|----------|
| Height of sensor | 108.2 mm |
| Length of sensor | 35 mm    |
| Width of sensor  | 27 mm    |

### Ambient conditions

|                                               |                                                    |
|-----------------------------------------------|----------------------------------------------------|
| Protection class                              | IP 65 to IEC/EN 60529<br>IP 67 to IEC/EN 60529     |
| Ambient temperature,<br>minimum               | -25 °C                                             |
| Ambient temperature,<br>maximum               | +70 °C                                             |
| Storage and transport<br>temperature, minimum | -25 °C                                             |
| Storage and transport<br>temperature, maximum | +85 °C                                             |
| Resistance to vibrations<br>to EN 60068-2-6   | 10 ... 55 Hz, amplitude 1 mm<br>30 g / 11 ms<br>II |

### Ambient conditions - Insulation value

|                                    |                    |
|------------------------------------|--------------------|
| Rated impulse withstand<br>voltage | 0.8 kV<br>III<br>3 |
|------------------------------------|--------------------|

### Electrical data

|                                                             |                     |
|-------------------------------------------------------------|---------------------|
| Voltage type                                                | DC (direct current) |
| No-load current                                             | 100 mA              |
| Operating current                                           | 600 mA              |
| Required rated short-<br>circuit current to EN<br>60947-5-1 | 100 A               |
| Switching frequency,<br>approx.                             | 3 Hz                |

### Electrical data - Fail-safe digital outputs

|                                                |        |
|------------------------------------------------|--------|
| Rated operating current<br>(safety outputs)    | 250 mA |
| Output current, (fail-safe<br>output), maximum | 0.3 A  |
| Versions                                       | p-type |

|                                    |        |
|------------------------------------|--------|
| Voltage drop $U_d$ , maximum       | 0.5 V  |
| Current leakage                    | 0.5 mA |
| Voltage, Utilisation category DC12 | 24 VDC |
| Current, Utilisation category DC12 | 0.3 A  |
| Voltage, Utilisation category DC13 | 24 VDC |
| Current, Utilisation category DC13 | 0.3 A  |

#### Electrical data - Diagnostic output

|                                    |        |
|------------------------------------|--------|
| Versions                           | p-type |
| Voltage drop $U_d$ , maximum       | 5 V    |
| Voltage, Utilisation category DC12 | 24 VDC |
| Current, Utilisation category DC12 | 0.1 A  |
| Voltage, Utilisation category DC13 | 24 VDC |
| Current, Utilisation category DC13 | 0.1 A  |

#### Electrical data - Electromagnetic compatibility (EMC)

IEC 61000-6-4  
IEC 61000-6-2

#### Pin assignment

|       |                           |
|-------|---------------------------|
| PIN 1 | 1A1 Ue: (1)               |
| PIN 2 | X1 Safety input 1         |
| PIN 3 | A2 GND                    |
| PIN 4 | Y1 Safety output 1        |
| PIN 5 | OUT Diagnostic output OUT |
| PIN 6 | X2 Safety input 2         |
| PIN 7 | Y2 Safety output 2        |
| PIN 8 | IN without function       |

#### Scope of delivery

|                      |                                       |
|----------------------|---------------------------------------|
| Included in delivery | Actuators must be ordered separately. |
|----------------------|---------------------------------------|

#### Accessory

CST 34-S-2  
CST 34-S-3  
CST 180-1  
CST 180-2  
CST 34-S-1  
PROTECT PSC1  
SRB-E-301ST  
SRB-E-201LC

## Notes

Note (General) Evaluation requirements: dual-channel safety input, suitable for p-type sensors with NO function. The safety-monitoring module must tolerate internal functional tests of the sensors with cyclic switch-off of the sensor outputs for max. 0.5 ms. Short-circuit recognition by the evaluation is not necessary.

## Ordering code

Product type description:

CSS (1)-34-(2)-(3)-(4)-M-(5)

(1)

**12** Actuation from top

**14** Actuation from side

(2)

**without** Standard version

**F0** Input for enabling pushbutton, suitable for automatic start

**F1** Input for reset pushbutton, with edge monitoring

(3)

**S** lateral active surface

**V** frontal active surface

(4)

**D** With diagnostic output

**SD** Serial diagnostic output

(5)

**L** with connecting cable

**ST** with connector

## Pictures


## Photo/Product/Catalogue



ID: kcsc3f09

| 273,0 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667  
Pixel - 72 dpi  
| 21,0 kB | .png | 74.083 x 49.389 mm - 210 x 140  
Pixel - 72 dpi


## Dimension/Product/Basic



ID: 1css3g01

| 4,4 kB | .png | 73.731 x 79.022 mm - 209 x 224 Pixel  
- 72 dpi  
| 50,7 kB | .cdr |  
| 204,8 kB | .jpg | 352.778 x 377.119 mm - 1000 x  
1069 Pixel - 72 dpi


## Graphic/Clipart



ID: kcsc3c06

| 932,0 b | .png | 74.083 x 35.983 mm - 210 x 102  
Pixel - 72 dpi  
| 16,0 kB | .cdr |

## Illustration/Product/Function



ID: kcsc3a02

| 46,4 kB | .cdr |  
| 321,9 kB | .jpg | 352.778 x 796.219 mm - 1000 x  
2257 Pixel - 72 dpi  
| 5,5 kB | .png | 74.083 x 167.217 mm - 210 x 474  
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 512021-01-31T06:07:51+01:000601Europe/BerlinSun, 31 Jan 2021 06:07:51

+010051amSunday.31am31Europe/BerlinCET0701Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:07:51

+010001am31