

# XUB9BPBWL5

photo-electric sensor - XUB - polarised - 90° -  
Sn 2m - 12..24VDC - cable 5m



## Main

Range of product	OsiSense XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XUB
Sensor design	Cylindrical M18
Detection system	Polarised reflex
Material	Metal
Line of sight type	90° lateral
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	PNP
Discrete output function	1 NC
Electrical connection	Cable
Cable length	5 m
Product specific application	-
Emission	Red polarised reflex
[Sn] nominal sensing distance	2 m polarised reflex need reflector XUZC50

## Complementary

Enclosure material	Nickel plated brass
Lens material	PMMA
Maximum sensing distance	3 m polarised reflex
Output type	Solid state
Output function governance	Light or dark programmable
Add on output	With alarm output
Cable composition	5 x 0.34 mm <sup>2</sup>
Wire insulation material	PvR
Cable outer diameter	6 mm
Status LED	1 LED (yellow) for output state 1 LED (red) for stability
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply voltage limits	10...38 V DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	<= 500 Hz
Maximum voltage drop	<1.5 V (closed state)
Current consumption	<= 50 mA no-load
Maximum delay first up	15 ms
Maximum delay response	1 ms
Maximum delay recovery	1 ms
Setting-up	Sensitivity adjustment with potentiometer
Diameter	18 mm
Depth	44 mm
Height	99 mm
Length	62 mm
Width	45 mm

Net weight	0.52 kg
Kit composition	Transmitter + receiver

## Environment

Product certifications	CSA UL CE
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C
Vibration resistance	7 gn (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	20 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP67 double insulation conforming to IEC 60529 IP65 double insulation conforming to IEC 60529

## Packing Units

Package 1 Weight	0.149 kg
Package 1 Height	1.300 dm
Package 1 width	0.660 dm
Package 1 Length	0.950 dm


## Contractual warranty

Warranty	18 months
----------	-----------

---

Dimensions

---




---

## Wiring Schemes

---

### PNP Outputs




BN : Brown  
BU : Blue  
BK : Black

---

Detection Curves

---



(Y) Ø of beam  
With reflector XUZY50