



EX-T3K335-02Y

- Metal enclosure
- Ex-Zone 1 and 21
- 40,5 mm x 76 mm x 38 mm
- 1 Cable entry M 20 x 1.5
- Mounting details to EN 50041
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°
- Actuation from bottom parallel to the switch, therefore only suitable for small housings.

Data

Ordering data

	EX-T3K335-02Y
	101212077
EAN (European Article Number)	4030661448633
eCl@ss number, Version 9.0	27-27-26-01

Approval - Standards

cULus
IECEX

Explosion protection

EN 60079-0
EN 60079-1
EN 60079-31
EN 60079-7
EN 60947-5-1
1
21
2D
2G
⊕ II 2G Ex d e IIC T6 Gb
⊕ II 2D Ex tb IIIC T80°C Db

General data

Product name	EX-T 335 angle roller lever 3K BG-GS-ET-15
Housing construction form	Norm construction design
Enclosure material	Zinc die-cast
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	320 g

General data - Features

Safety functions	Yes
Number of safety contacts	2

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Angle roller lever
Mechanical life, minimum	1,000,000 Operations
Impact energy, maximum	7 J
Actuating force, minimum	17 N
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note (Switchover time)	Switchover time in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	7 mm
Cable cross-section of the cable glands, maximum	12 mm
Cable section, minimum	1 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	121.5 mm
Length of sensor	38 mm
Width of sensor	58.3 mm

Ambient conditions

	IP65
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum (Cable section 1mm ²)	+50 °C
Ambient temperature, maximum (Cable section 2.5mm ²)	+55 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	5 A
Switching element	Opener (NC)
Switching principle	Slow action
Bounce duration, maximum	3 ms
Switching frequency	1,800 /h

Ordering code

Product type description:

EX-T(1) 335-(2)Y(3)-(4)-(5)

(1)

S	Plunger S
R	Roller plunger R
H	Roller lever H
10H	Rod lever 10H
7H	Roller lever 7H
7H-2138	Roller lever 7H for position switches with safety function
1K	Offset roller lever 1K
3K	Angle roller lever 3K

(2)

11	1 NO contacts/1 NC contact
02	2 NC contact

20 2 NO contacts (not suitable for safety applications)

(3)

UE Slow action with overlapping contacts

without Slow action with staggered contacts

(4)

2138 Roller lever 7H for position switches with safety function

(5)

RMS Roller made from brass

Pictures

Photo/Product/Catalogue




ID: k335kf02

| 98,9 kB | .png | 74.083 x 143.581 mm - 210 x 407
Pixel - 72 dpi

| 540,4 kB | .jpg | 185.914 x 360.892 mm - 527 x 1023
Pixel - 72 dpi

Dimension/Product/Basic




ID: k-335g01

| 126,8 kB | .jpg | 352.778 x 248.708 mm - 1000 x 705
Pixel - 72 dpi

| 4,1 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi

| 27,9 kB | .cdr |

Dimension/Product/Basic




ID: 1xzm1g07

| 2,5 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 46,3 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

Diagramm/Product/Travel

ID: kk335s31




| 1,7 kB | .png | 74.083 x 22.931 mm - 210 x 65 Pixel - 72 dpi

| 44,2 kB | .jpg | 352.778 x 109.714 mm - 1000 x 311 Pixel - 72 dpi

| 20,8 kB | .cdr |

Dimension/Product/Actuator



ID: 1k336g02

| 60,3 kB | .cdr |

| 8,9 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi

| 94,1 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 292021-01-31T17:44:29+01:000501Europe/BerlinSun, 31 Jan 2021 17:44:29

+010029pmSunday.31pm31Europe/BerlinCET4401Europe/BerlinJanuary2021Sun, 31 Jan 2021 17:44:29

+010001pm31