

EX-ZS 355-02Z-3G/D



- Ex certified
- Metal enclosure
- Ex-Zone 2 and 22
- 66,7 mm x 76 mm x 38 mm
- 3 cable entries M 20 x 1.5
- Mounting details to EN 50041
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°
- Including Ex-certified screwed cable gland and screw plug
- Snap action with constant contact pressure up to switching point

Data

Ordering data

EX-ZS 355-02Z-3G/D

103008395

EAN (European Article Number)

4030661453224

Explosion protection

EN 60079-15

EN 60079-31

IEC 60079-0

22

2

3D

3G

⊕ II 3G Ex nC IIC T5 Gc X

⊕ II 3D Ex tc IIIC T90°C Dc X

Manufacturer declaration

ATEX Zone 2 and 22

General data

Product name

EX-355 plunger S

	IEC 60947-5-1
	BG-GS-ET-15
Housing construction form	Norm construction design
	B
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	308 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	0
Number of safety contacts	2

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Plunger
Mechanical life, minimum	30,000,000 Operations
Impact energy, maximum	1 J
Actuating force, minimum	12 N
Actuating speed, maximum	0.5 m/s
Note Bounce duration	Bounce duration in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	7 mm
Cable cross-section of the cable glands, maximum	12 mm
	0.75 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	103.5 mm
Length of sensor	38 mm
Width of sensor	40.5 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	Opener (NC)
Switching principle	Snap switch element
Switching frequency	5,000 /h
Switchover time, maximum	2 ms

Ordering code

Product type description:

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

7H-2138 Roller lever 7H for position switches with safety function

1K Offset roller lever 1K

3K Angle roller lever 3K

11	1 NO contacts/1 NC contact
02	2 NC contact
20	2 NO contacts (not suitable for safety applications)
01/01	1 NC contact left / 1 NC contact right
12	1 NO contact/2 NC contacts
03	3 NC contact

H Slow action with staggered contacts


UE Slow action with overlapping contacts

1297 Enclosure with transverse slotted holes

2138 Roller lever 7H for position switches with safety function

1637 Gold-plated contacts

Photo/Product/Catalogue



| 111,4 kB | .png | 74.083 x 112.183 mm - 210 x 318
Pixel - 72 dpi

| 275,1 kB | .jpg | 127.353 x 192.969 mm - 361 x 547
Pixel - 72 dpi

ID: k-355g01

| 133,4 kB | .jpg | 352.778 x 215.9 mm - 1000 x 612
Pixel - 72 dpi
| 30,4 kB | .cdr |
| 4,4 kB | .png | 74.083 x 45.156 mm - 210 x 128 Pixel
- 72 dpi

Diagramm/Product/Travel

