



TQ 700-11 S

- 2 Contacts
- vertical mounting
- 1 Cable entry M20
- wire pull detection
- Thermoplastic enclosure
- Large wiring compartment
- Twisting of towing eye not possible

Data

Ordering data

	TQ 700-11 S
	101217092
EAN (European Article Number)	4030661410647
eCl@ss number, Version 9.0	27-27-06-07

Approval - Standards

TÜV
EAC

General data

	TQ 700 S
	IEC/EN 60947-5-1
Enclosure material	Glass-fibre, thermoplastic
Material of the contacts, electrical	Silver
Material of the cover	Glass-fibre, thermoplastic
Gross weight	200 g

General data - Features

Number of openers	1
Number of shutters	1

Mechanical data

Mechanical life, minimum	1,000,000 Operations
--------------------------	----------------------

Actuating force, minimum	74.8 N
Actuating force, maximum	101.2 N

Mechanical data - Connection technique

Terminal Connector	Screw connection 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Width	40.5 mm
Height	160 mm
Depth	42.5 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Switching element	NO contact, NC contact
Switching principle	Creep circuit element

Ordering code

Product type description:

TQ 700-(1) S

(1)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts

Pictures


Photo/Product/Catalogue



ID: ktq70f01

| 38,6 kB | .png | 74.083 x 111.125 mm - 210 x 315
Pixel - 72 dpi
| 493,4 kB | .jpg | 352.778 x 529.167 mm - 1000 x
1500 Pixel - 72 dpi


Dimension/Product/Basic



ID: 1tq-7g03

| 192,2 kB | .cdr |
| 10,0 kB | .png | 74.083 x 51.506 mm - 210 x 146
Pixel - 72 dpi
| 106,8 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695
Pixel - 72 dpi


Diagramm/Product/Travel



ID: ktq70s01

| 1,6 kB | .png | 74.083 x 22.578 mm - 210 x 64 Pixel -
72 dpi
| 24,3 kB | .cdr |
| 34,9 kB | .jpg | 352.778 x 106.892 mm - 1000 x 303
Pixel - 72 dpi

Graphic/Product/Contact



ID: ktf--k01

| 16,0 kB | .cdr |
| 54,5 kB | .jpg | 352.778 x 195.439 mm - 1000 x 554
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 362021-01-31T16:41:36+01:00401Europe/BerlinSun, 31 Jan 2021 16:41:36

+010036pmSunday.31pm31Europe/BerlinCET4101Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:41:36

+010001pm31