

Technical data sheet

Signaling column

Part no.: 50144676

A7-V1-MP2-BZ2-S-DS-ROG-T-100

Contents

- Technical data
- Dimensioned drawings
- Electrical connection
- Notes
- Accessories



Figure can vary



Technical data

Basic data

Series	A7
Type of signaling	Optical and acoustic

Electrical data

Life expectancy	> 100,000 h
Performance data	
Supply voltage U_B	24 V, DC, 10 %
Current consumption, max.	160 mA

Connection

Number of connections	1 Piece(s)
Notes	Protected against accidental interchanges: Actuation of the colors is performed via PINs, thus, the calotte position can be freely selected (see operating instructions).

Connection 1

Function	Voltage supply
Type of connection	Terminal
Cable length	1,500 mm
Number of conductors	6 -wire

Connection 2

Type of connection	Open end
--------------------	----------

Mechanical data

Design	Cylindrical
Dimension (Ø x L)	70 mm x 430 mm
Housing material	Metal
	Plastic, PC-ABS
Net weight	680 g
Housing color	Black
	Gray
Design of mounting device	Base mounting
Type of fastening, at system	Screw type / horizontal
	Screw type / vertical
Type of mounting device	180°, adjustable in intervals of 15°
Type of illuminant	LED/24V
Lens modules	4 pieces, ready-made
Signal image	Continuous light
Angle of radiation	360°
Sequence of the modules (ascending)	Green, orange, red, single sound buzzer

Certifications

Degree of protection	IP 66, Only when mounted on a housing with the same degree of protection
Certifications	CE
	CSA

Acoustic data


Tone type	Continuous tone
Sound pressure	105 dB
Number of tones	1 Piece(s)

Classification

Customs tariff number	85318070
eCl@ss 8.0	27371230
eCl@ss 9.0	27371220
eCl@ss 10.0	27371230
eCl@ss 11.0	27371230
ETIM 5.0	EC000232
ETIM 6.0	EC000232

Dimensioned drawings

All dimensions in millimeters



Electrical connection

Connection 1

Function	Voltage supply
Type of connection	Terminal
Type of terminal	Tension spring technology
Cable length	1,500 mm
Sheathing material	PVC
Cable color	Gray
Number of conductors	6 -wire
Wire cross section	0.34 mm ²

Electrical connection

Conductor color	Conductor assignment
Black	GND
Red	Light color: red
Green	Light color: orange
Orange	Light color: red
White	Light color: blue
Blue	Light color: blue

Connection 2

Type of connection	Open end
--------------------	----------

Notes





Observe intended use!



- ⚠ This product is not a safety sensor and is not intended as personnel protection.
- ⚠ The product may only be put into operation by competent persons.
- ⚠ Only use the product in accordance with its intended use.

Accessories

Mounting technology - Mounting brackets

	Part no.	Designation	Article	Description
	50142896	A7-MW2	Signaling column element	Design: L shape Version: Angle, L-shape Fastening, at system: Through-hole mounting
	50143660	A7-MW2.5	Signaling column element	Design: L shape Version: Angle, L-shape Fastening, at system: Through-hole mounting

Note



- ⓘ A list with all available accessories can be found on the Leuze website in the Download tab of the article detailed page.