

PS226-T11-N200



- Design to EN 50047
- cable entry 2 x M20 x 1,5
- length adjustable in 2 mm steps
- Lever angle adjustable in 15° steps
- thermoplastic enclosure with foldable latching cover
- Simple and quick to adjust the control elements by 45°.
- Quick connection technology as connection terminals rotated by 45°

Data

Ordering data

PS226-T11-N200

103015092

EAN (European Article Number)

4030661502175

Approval - Standards

cULus

CCC

EAC

General data

Product name

PS226 with roller lever N200

IEC 60947-5-1

Housing construction form

Norm construction design

Enclosure material

Plastic, glass-fibre-reinforced

Material of the contacts, electrical

Silver

Gross weight

145.4 g

General data - Features

Safety functions

Yes

Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Roller lever N200
Mechanical life, minimum	10,000,000 Operations
Positive break force, minimum	40 N
Actuating speed, minimum	60 mm/min
Actuating speed, maximum	1 m/s

Mechanical data - Connection technique

Terminal Connector	Screw connection
	0.34 mm ²
	1.5 mm ²

Mechanical data - Dimensions

Height of sensor	150.5 mm
Length of sensor	33 mm
Width of sensor	59 mm

Ambient conditions

	IP66
	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	400 A
Utilisation category AC-15	240 VAC
Utilisation category AC-15	3 A

Utilisation category DC-13	24 VDC
Utilisation category DC-13	3 A
Switching element	1 NO contact, 1 NC contacts
Switching principle	Creep circuit element
Switching frequency	5,000 /h

Ordering code

Product type description:

PS2(2)-(3)-(4)-(5)-(6)-(7)-(8)-(9)-(10)-(11)-
(12)

(1)

without non-EX version

EX Types of protection Ex d and t, to Zone 1/21

EXI Types of protection Ex i and t, up to Zone 1/21

(2)

5 Metal enclosure

216 Thermoplastic enclosure

226 Plastic housing with 2 cable entries

(3)

without L-hole (standard)

L elongated hole

(4)

Z11 Snap action 1 NO contact / 1 NC contact

Z02 Snap action 2 NC contacts

Z12 Snap action 1 NO contact / 2 NC contact

Z11R Snap action 1 NO contact / 1 NC contact with latching

Z01R Snap action 1 NC contact with latching

Z02R Snap action 2 NC contacts with latching

T11 Slow action 1 NO contact / 1 NC contact

T02 Slow action 2 NC contacts

T20 Slow action 2 NO contact

T12 Slow action 1 NO contact / 2 NC contact

T21 Slow action 2 NO contact / 1 NC contact

T03 Slow action 3 NC contacts

T11UE Slow action 1 NO contact / 1 NC contact with overlapping contacts

T02H Slow action 2 NC contacts with staggered contacts

T11K Slow action 1 NO contact + 1 NC contact - short-stroke

T10 Slow action 1 NO contact

T02K Slow action 2 NO contacts short-stroke

T20H Slow action 2 NO contacts staggered

(5)

without Contacts silver plated (Standard)

A1 Gold contacts 0,3 µm

A2 Gold contacts 1,0 µm

A3 Gold contacts 3,0 µm

(6)

without without indication light

G integrated status display

(7)

without Cable entry M20

M16 cable entry M16

ST Connector plug M12 - plastic - bottom

STR Connector plug M12, right

STL Connector plug M 12, left

STM Connector plug M12, metal

(8)

S200 plunger S200 Ø 6 mm

S210 Plunger Ø 8,6 mm

S211 Plunger Ø 10,3 mm

S221 Plunger Ø 9,8 mm

R200 Roller plunger R200

R201 Roller plunger - stainless steel roller Ø 9,5mm

R210 Roller plunger - plastic roller Ø 12mm

K201 Roller plunger - stainless steel roller - width 5,3 mm - Ø 12mm

K200 Offset roller lever - plastic roller- width 5.3 mm - Ø 12 mm

K201 Roller plunger - stainless steel roller - width 5,3 mm - Ø 12mm

K210 Offset roller lever - plastic roller- width 5mm - Ø 14mm

K211 Offset roller lever - stainless steel roller - width 5mm - Ø 14mm

K220 Offset roller lever - plastic roller- width 7.6 mm - Ø 14 mm

K230 Angle roller lever - plastic roller Ø 14 mm

K231 Roller plunger - stainless steel roller Ø 14mm (Standard)

K240 Angle roller lever with plastic roller Ø 22 mm - right-bent

K250 Angle roller lever with plastic roller Ø 22 mm - left-bent

H200 Roller lever - plastic roller Ø 16 m - lever length 24 mm

H202 Roller lever - brass roller Ø 16mm - lever length 24mm (Standard)

H230 Roller lever - plastic roller Ø 16mm - lever length 28 mm

H232 Roller lever - brass roller Ø 16mm - lever length 28 mm

H236 Roller lever - rubber roller Ø 16mm - lever length 28 mm

N200 Roller lever 2 mm Toothing (24...26mm) - Plastic roller Ø 20 mm - Width 9.8 mm

N201 Roller lever adjustable in 2 mm steps (24...66mm) - stainless steel roller Ø 20mm - width 9,8 mm

N202 Roller lever - adjustable in 2 mm steps (24...66mm) - brass roller Ø 20mm - width 9,8 mm

N206 Roller lever - adjustable in 2 mm steps (24...66mm) - rubber roller Ø 50mm - width 16 mm

N210	Roller lever - adjustable in 2 mm steps (24...66mm) - plastic roller Ø 20mm - width 5 mm - long-angled - locking washer
N280	Roller lever -adjustable in 2 mm steps (24...66mm) - plastic roller Ø 20mm - width 5 mm - long - locking washer
J200	Rod lever - plastic - 200mm -Ø 6mm
J201	Rod lever - stainless steel - 200mm -Ø 6mm (Standard)
J203	Rod lever - aluminium - 200mm -Ø 6mm
F230	Spring rod - stainless steel - 150.4 mm
F231	Spring rod - stainless steel - 70.2 mm
A200	Special actuating bolt - plastic - valve control

(9)

without no intent rotation (Standard)

U1	intent rotation 45°
U2	intent rotation 90°
U3	intent rotation 135°
U4	intent rotation 180°
U5	intent rotation 225°
U6	intent rotation 275°
U7	intent rotation 315°

(10)

without no lever rotation (Standard)

X1	lever rotation 15°
X2	lever rotation 30°
X3	lever rotation 45°
X4	lever rotation 60°
X5	lever rotation 75°
X6	lever rotation 90°
X7	lever rotation 105°
X8	lever rotation 120°
X9	lever rotation 135°
X10	lever rotation 150°
X11	lever rotation 165°
X12	lever rotation 180°
X13	lever rotation 195°
X14	lever rotation 210°
X15	lever rotation 225°
X16	lever rotation 240°
X17	lever rotation 255°
X18	lever rotation 270°
X19	lever rotation 285°
X20	lever rotation 300°
X21	lever rotation 315°
X22	lever rotation 330°

X23 lever rotation 345°

(11)

without Roller outside (Standard)

I Roller inside

(12)

without -30...+80°C (Standard)

T -40...+80°C

(13)

(14)

without Zone 2 and 22

3GD Zone 2 and 22

2D Zone 21

3D Zone 22

Pictures

Photo/Product/Catalogue



ID: kps1nf07

| 337,7 kB | .jpg | 352.778 x 511.528 mm - 1000 x 1450 Pixel - 72 dpi

| 32,9 kB | .png | 74.083 x 107.244 mm - 210 x 304 Pixel - 72 dpi

Photo/Product/Catalogue




ID: kps2nf03

| 50,9 kB | .png | 74.083 x 125.942 mm - 210 x 357 Pixel - 72 dpi

| 764,7 kB | .jpg | 352.778 x 600.075 mm - 1000 x 1701 Pixel - 72 dpi


Dimension/Product/Basic



ID: kps2xg04

| 167,8 kB | .jpg | 352.778 x 304.447 mm - 1000 x 863
Pixel - 72 dpi
| 6,5 kB | .png | 74.083 x 63.853 mm - 210 x 181 Pixel
- 72 dpi


Diagramm/Product/Travel



ID: kps11s58

| 2,1 kB | .png | 74.083 x 30.339 mm - 210 x 86 Pixel - 72 dpi
| 69,1 kB | .jpg | 352.778 x 144.639 mm - 1000 x 410 Pixel - 72 dpi


Graphic/Product/Contact



ID: kps2xk09

| 57,7 kB | .jpg | 352.778 x 110.067 mm - 1000 x 312
Pixel - 72 dpi

Dimension/Product/Actuator



ID: kps11b10

| 13,7 kB | .png | 74.083 x 72.672 mm - 210 x 206
Pixel - 72 dpi

| 195,0 kB | .jpg | 352.778 x 383.469 mm - 1000 x
1087 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 502021-01-31T02:48:50+01:000201Europe/BerlinSun, 31 Jan 2021 02:48:50

+010050amSunday.31am31Europe/BerlinCET4801Europe/BerlinJanuary2021Sun, 31 Jan 2021 02:48:50

+010001am31