



EFK10.2

- Cage clamps
- 21-22 (Contact labelling)
- Mounting flange position 2

Data

Ordering data

	EFK10.2
	101022276
EAN (European Article Number)	4030661463674
eCl@ss number, Version 9.0	27-37-13-02

Approval - Standards

cULus
CCC
EAC

General data

Product name	Contact element EFK EN 60947-5-1 IEC/EN 60947-1
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Contact labelling	21-22
Gross weight	35 g

General data - Features

Number of openers	1
-------------------	---

Mechanical data

Installation instructions	pluggable
---------------------------	-----------

Mechanical life, minimum	10,000,000 Operations
positive break travel	2 mm
Contact opening	1 mm
Note Bounce duration	Bounce duration at an Actuating speed of 100mm/s 2

Mechanical data - Connection technique

Terminal Connector	Cage clamps, WAGO-Cage-Clamp 2 x 0.08 mm ² 2 x 1.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Width	10 mm
Length	46 mm
Depth	51 mm

Ambient conditions

	IP40
	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C
	110 g / 4 ms
Resistant to vibration	Resistance to vibration: 20 g / 10...200 Hz

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A
	≥ 5 V / ≥ 3.2 mA
Switching element	Opener (NC)
Switching principle	Slow action
Bounce duration, maximum	5 ms
Switching frequency	1,200 /h

Pictures

Photo/Product/Catalogue



ID: kefkf02

| 33,1 kB | .png | 74.083 x 74.083 mm - 210 x 210

Pixel - 72 dpi

| 380,4 kB | .jpg | 352.425 x 352.778 mm - 999 x 1000

Pixel - 72 dpi

Diagramm/Product/Travel

ID: krf--s01



| 19,6 kB | .jpg | 352.778 x 80.433 mm - 1000 x 228


Pixel - 72 dpi

| 18,5 kB | .cdr |

| 1.020,0 b | .png | 74.083 x 16.933 mm - 210 x 48

Pixel - 72 dpi

Illustration/Product/Function



ID: krf--a07

| 4,3 kB | .png | 73.731 x 124.531 mm - 209 x 353

Pixel - 72 dpi

| 19,0 kB | .cdr |

| 184,6 kB | .jpg | 352.778 x 594.431 mm - 1000 x

1685 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 292021-01-31T14:31:29+01:000201Europe/BerlinSun, 31 Jan 2021 14:31:29

+010029pmSunday.31pm31Europe/BerlinCET3101Europe/BerlinJanuary2021Sun, 31 Jan 2021 14:31:29

+010001pm31