

## PS116-Z11-L200-N200



- Symmetric enclosure
- Thermoplastic enclosure
- Pre-wired cable bottom, 2
- Protection class IP66, IP67
- length adjustable in 2 mm steps
- Lever angle adjustable in 15° steps
- Actuator heads can be repositioned by 8 x 45°
- Snap action 1 Normally open contact (NO) / 1 Opener (NC)

### Data

#### Ordering data

|                               |                     |
|-------------------------------|---------------------|
|                               | PS116-Z11-L200-N200 |
|                               | 103006646           |
| EAN (European Article Number) | 4030661442778       |
| eCl@ss number, Version 9.0    | 27-27-06-01         |

#### Approval - Standards

cULus  
CCC  
EAC

#### General data

|                                      |                                                                         |
|--------------------------------------|-------------------------------------------------------------------------|
| Product name                         | PS116 roller lever N200                                                 |
|                                      | IEC 60947-5-1                                                           |
| Terminal (mechanical)                | bottom                                                                  |
| Housing construction form            | Norm construction design                                                |
| Enclosure material                   | Plastic, glass-fibre reinforced thermoplastic, zinc die-cast, chromated |
| Material of the contacts, electrical | Silver                                                                  |
| Gross weight                         | 247 g                                                                   |

## General data - Features

|                              |     |
|------------------------------|-----|
| Safety functions             | Yes |
| Number of auxiliary contacts | 1   |
| Number of safety contacts    | 1   |

## Safety appraisal

|              |             |
|--------------|-------------|
|              | ISO 13849-1 |
| Mission Time | 20 Year(s)  |

## Safety appraisal - Safety outputs

|                                   |                       |
|-----------------------------------|-----------------------|
| B10d Normally-closed contact (NC) | 20,000,000 Operations |
|-----------------------------------|-----------------------|

## Mechanical data

|                           |                       |
|---------------------------|-----------------------|
| Actuating element         | Roller lever N200     |
| Mechanical life, minimum  | 10,000,000 Operations |
| Actuating speed, minimum  | 240 mm/min            |
| Actuating speed, maximum  | 1 m/s                 |
| Actuating torque, minimum | 0.2 Nm                |
| Positive break torque     | 0.6 Nm                |

## Mechanical data - Connection technique

|                    |                             |
|--------------------|-----------------------------|
| Terminal Connector | Cable, 4-pole               |
| Length of cable    | 2 m                         |
| Wire cross-section | 0.5 mm <sup>2</sup><br>LiYY |

## Mechanical data - Dimensions

|                    |         |
|--------------------|---------|
| Height of sensor   | 139 mm  |
| Length of sensor   | 16.6 mm |
| Width of sensor    | 31 mm   |
| Diameter of Castor | 20 mm   |

## Ambient conditions

|                              |              |
|------------------------------|--------------|
|                              | IP66<br>IP67 |
| Ambient temperature, minimum | -30 °C       |
| Ambient temperature, maximum | +80 °C       |

## Ambient conditions - Insulation value

|                                 |      |
|---------------------------------|------|
| Rated impulse withstand voltage | 4 kV |
|---------------------------------|------|

## Electrical data

|                                                      |                        |
|------------------------------------------------------|------------------------|
| Thermal test current                                 | 5 A                    |
| Required rated short-circuit current to EN 60947-5-1 | 1,000 A                |
| Utilisation category AC-15                           | 240 VAC                |
| Utilisation category AC-15                           | 3 A                    |
| Utilisation category DC-13                           | 24 VDC                 |
| Utilisation category DC-13                           | 1.5 A                  |
| Switching element                                    | NO contact, NC contact |
| Switching principle                                  | Snap switch element    |
| Bounce duration, maximum                             | 3 ms                   |
| Switching frequency                                  | 5,000 /h               |
| Switchover time, maximum                             | 5.5 ms                 |

## Ordering code

Product type description:

PS116-(1)-(2)-(3)-(4)

(1)

- Z11** Snap action 1 NO contact / 1 NC contact
- Z02** Snap action 2 NC contacts
- Z12** Snap action 1 NO contact / 2 NC contact
- Z11R** Snap action 1 NO contact / 1 NC contact with latching
- Z02R** Snap action 2 NC contacts with latching
- Z12R** Snap action 1 NO contact / 2 NC contact with latching
- T11** Slow action 1 NO contact / 1 NC contact
- T02** Slow action 2 NC contacts
- T20** Slow action 2 NO contact
- T12** Slow action 1 NO contact / 2 NC contact
- T21** Slow action 2 NO contact / 1 NC contact
- T03** Slow action 3 NC contacts
- T11UE** Slow action 1 NO contact / 1 NC contact with overlapping contacts
- T02H** Slow action 2 NC contacts with staggered contacts

(2)

- L200** Connecting cable bottom, cable length 2 m
- LR200** Connecting cable right, cable length 2 m
- ST** Connector plug M12 - plastic - bottom
- STR** Connector plug M12, right

(3)

**S200** plunger S200 Ø 6 mm

**R200** Roller plunger R200

**K200** Offset roller lever - plastic roller- width 5.3 mm - Ø 12 mm

**K210** Offset roller lever - plastic roller- width 5mm - Ø 14mm

**K230** Angle roller lever - plastic roller Ø 14 mm

**K240** Angle roller lever with plastic roller Ø 22 mm - right-bent

**K250** Angle roller lever with plastic roller Ø 22 mm - left-bent

**H200** Roller lever - plastic roller Ø 16 m - lever length 24 mm

**N200** Roller lever 2 mm Toothing (24...26mm) - Plastic roller Ø 20 mm - Width 9.8 mm

**J200** Rod lever - plastic - 200mm -Ø 6mm

(4)

**0** Material Castor/Lever: Plastic

**1** Material Castor/Lever: Stainless steel

**2** Material Castor/Lever: Brass

**3** Material Castor/Lever: Aluminium

**4** Material Castor/Lever: Steel

## Pictures

### Photo/Product/Catalogue



ID: kps1nf02


| 61,4 kB | .png | 74.083 x 209.197 mm - 210 x 593

Pixel - 72 dpi

| 850,1 kB | .jpg | 352.778 x 997.303 mm - 1000 x

2827 Pixel - 72 dpi

### Dimension/Product/Basic



ID: kps11g03


| 6,3 kB | .png | 74.083 x 113.242 mm - 210 x 321

Pixel - 72 dpi

| 199,2 kB | .jpg | 352.425 x 539.75 mm - 999 x 1530

Pixel - 72 dpi

### Diagramm/Product/Travel



ID: kps11s55

| 2,7 kB | .png | 74.083 x 40.217 mm - 210 x 114 Pixel  
- 72 dpi

| 95,5 kB | .jpg | 352.778 x 191.911 mm - 1000 x 544  
Pixel - 72 dpi

## Graphic/Product/Contact


(3) BN 13 — 14 PK (4)  
(1) YE 21 — 22 WH (2)

ID: kps16k02

| 1,3 MB | .cdr |

| 56,4 kB | .jpg | 352.778 x 64.206 mm - 1000 x 182  
Pixel - 72 dpi

## Dimension/Product/Actuator



ID: kps11b10

| 13,7 kB | .png | 74.083 x 72.672 mm - 210 x 206  
Pixel - 72 dpi

| 195,0 kB | .jpg | 352.778 x 383.469 mm - 1000 x  
1087 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 532021-01-31T02:03:53+01:000201Europe/BerlinSun, 31 Jan 2021 02:03:53

+010053amSunday.31am31Europe/BerlinCET0301Europe/BerlinJanuary2021Sun, 31 Jan 2021 02:03:53

+010001am31