



EX-T4VH335-11Y

- Metal enclosure
- Ex-Zone 1 and 21
- 40,5 mm x 76 mm x 38 mm
- 1 Cable entry M 20 x 1.5
- Mounting details to EN 50041
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	EX-T4VH 335-11Y
	101212058
EAN (European Article Number)	4030661440095
eCl@ss number, Version 9.0	27-27-26-01

Approval - Standards

cULus
IECEX

Explosion protection

EN 60079-0
EN 60079-1
EN 60079-31
EN 60079-7
EN 60947-5-1
1
21
2D
2G
⊕ II 2G Ex d e IIC T6 Gb
⊕ II 2D Ex tb IIIC T80°C Db

General data

Product name	EX-T 335 roller lever H BG-GS-ET-15
--------------	--

Housing construction form	Norm construction design
Enclosure material	A
Enclosure coating material	Zinc die-cast
Material of the contacts, electrical	painted
Lever material	Silver
Roller material	Metal film
Gross weight	Plastic
	400 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	1,000,000 Operations
Impact energy, maximum	7 J
Actuating speed, maximum	2.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note (Switchover time)	Switchover time in accordance with actuating speed
Actuating torque, minimum	0.3 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	7 mm
Cable cross-section of the cable glands, maximum	12 mm
Cable section, minimum	1 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	134 mm
Length of sensor	60.6 mm
Width of sensor	40.5 mm

Ambient conditions

	IP65
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum (Cable section 1mm ²)	+50 °C
Ambient temperature, maximum (Cable section 2.5mm ²)	+55 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	5 A
Switching element	NO contact, NC contact
Switching principle	Creep circuit element
Bounce duration, maximum	3 ms
Switching frequency	1,800 /h

Ordering code

Product type description:

EX-T(1) 335-(2)Y(3)-(4)-(5)

(1)

S	Plunger S
R	Roller plunger R
H	Roller lever H
10H	Rod lever 10H
7H	Roller lever 7H
7H-2138	Roller lever 7H for position switches with safety function
1K	Offset roller lever 1K
3K	Angle roller lever 3K

(2)

11	1 NO contacts/1 NC contact
02	2 NC contact

20 2 NO contacts (not suitable for safety applications)

(3)

UE Slow action with overlapping contacts

without Slow action with staggered contacts

(4)

2138 Roller lever 7H for position switches with safety function

(5)

RMS Roller made from brass

Pictures

Photo/Product/Catalogue



ID: k335hf01


| 165,3 kB | .png | 74.083 x 197.556 mm - 210 x 560

Pixel - 72 dpi

| 524,1 kB | .jpg | 143.581 x 383.469 mm - 407 x 1087

Pixel - 72 dpi

Dimension/Product/Basic



ID: k-335g01


| 126,8 kB | .jpg | 352.778 x 248.708 mm - 1000 x 705

Pixel - 72 dpi

| 4,1 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi

| 27,9 kB | .cdr |

Dimension/Product/Basic




ID: 1xzm1g07

| 2,5 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 46,3 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

Diagramm/Product/Travel

ID: kh335s27




| 69,1 kB | .jpg | 352.778 x 112.889 mm - 1000 x 320 Pixel - 72 dpi

| 21,5 kB | .cdr |

| 2,3 kB | .png | 74.083 x 23.636 mm - 210 x 67 Pixel - 72 dpi

Dimension/Product/Actuator

ID: 1h336g01



| 84,5 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi

| 65,6 kB | .cdr |

| 4,1 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 522021-01-31T17:41:52+01:000501Europe/BerlinSun, 31 Jan 2021 17:41:52

+010052pmSunday.31pm31Europe/BerlinCET4101Europe/BerlinJanuary2021Sun, 31 Jan 2021 17:41:52

+010001pm31