

AZM 161SK-12/12RKTD/EU-024



- Long life
- 6 Contacts
- Double-insulated
- 130 mm x 90 mm x 30 mm
- Thermoplastic enclosure
- Large wiring compartment
- cable entries 4 M 16 x 1.5
- Emergency exit, cover-side and Manual release, rear
- Interlock with protection against incorrect locking.

Data

Ordering data

	AZM 161SK-12/12RKTD/EU-024
	101187869
EAN (European Article Number)	4030661357195
eCl@ss number, Version 9.0	27-27-26-03

Approval - Standards

cULus
CCC
EAC

General data

	AZM 161
	EN 60947-5-1
	BG-GS-ET-19
Coding level according to ISO 14119	Low
Active principle	electromechanical
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	475 g

General data - Features

Power to unlock	Yes
-----------------	-----

Emergency exit	Yes
Manual release	Yes
Number of actuating directions	3
Number of auxiliary contacts	2
Number of safety contacts	4

Safety appraisal

ISO 13849-1

Mission Time	20 Year(s)
--------------	------------

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
B10d Normally open contact (NO)	1,000,000 Operations

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Actuating play in direction of actuation	5.5 mm
Clamping force in accordance with ISO14119 F_{zh}	2,000 N
Latching force	30 N
positive break travel	10 mm
Positive break force, minimum	20 N
Actuating speed, maximum	2 m/s

Mechanical data - Connection technique

Terminal Connector	Screw terminals
	1 x 0.25 mm ²
	1 x 1.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	90 mm
Length of sensor	30 mm
Width of sensor	130 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage 4 kV

Electrical data

Thermal test current	6 A
Rated control voltage	24 VAC/DC
Required rated short-circuit current to EN 60947-5-1	1,000 A
Electrical power consumption, maximum	10 W
Switching element	NO contact, NC contact
Switching principle	Creep circuit element
Switching frequency	1,000 /h

Electrical data - Safety contacts

Voltage, Utilisation category AC15 230 VAC

Current, Utilisation category AC-15 4 A

Voltage, Utilisation category DC13 24 VDC

Current, Utilisation category DC13 2.5 A

Electrical data - Auxiliary contacts

Voltage, Utilisation category AC15 230 VAC

Current, Utilisation category AC-15 4 A

Voltage, Utilisation category DC13 24 VDC

Current, Utilisation category DC13 2.5 A

Other data

Note (applications)	sliding safety guard
	removable guard
	hinged safety guard

Scope of delivery

Included in delivery Actuators must be ordered separately.

Notes

Note (Emergency exit)	The emergency exit is used where an intervention in an already locked hazardous area is required
	Emergency exit by pressing the red push button
	Resetting by pulling on the latched button
	Top-side (ordering suffix -TD) or rear-side (ordering suffix -TU) mounting possible
Note (Manual release)	For maintenance, installation, etc.
	For manual release using M5 triangular key, available as accessory
	Top-side (ordering suffix -ED) or rear-side (ordering suffix -EU) mounting possible
Note (Emergency exit, Manual release)	A combination of manual release and emergency exit in different mounting directions is only possible for the following variants: -ED/-TU and -TD/-EU

Ordering code

Product type description:

AZM 161 (1)-(2)(3)K(4)-(5)-(6)(7)

(1)

SK Screw connection

CC Cage clamps

ST Connector M12, 8 and 4 pole (only for Us: 24 VAC/DC)

(2)

11/03 1 NO contacts / 4 NC contacts (connector version)

12/03 1 NO contacts/5 NC contact

12/11 2 NO contacts / 3 NC contacts (connector version)

11/12 2 NO contacts / 3 NC contacts (connector version)

12/12 2 NO contacts/4 NC contacts

(3)

without Latching force 5 N

R Latching force 30 N

(4)

without Power to unlock

A Power to lock

(5)

without Lateral manual release

ED Manual release on the cover side

EU Manual release on the rear side

T Lateral emergency exit

TD Emergency exit on the cover side

TU Emergency exit on the rear side

N Emergency release

(6)

024 Us: 24 VAC/DC

110/230 Us: 110/230 VAC

(7)

G with LED (only for Us: 24 VAC/DC)

Pictures


Photo/Product/Catalogue



ID: kazm1f03

| 36,6 kB | .png | 74.083 x 55.739 mm - 210 x 158
Pixel - 72 dpi
| 698,5 kB | .jpg | 352.778 x 265.289 mm - 1000 x 752
Pixel - 72 dpi


Dimension/Product/Basic



ID: 1azm1g09

| 3,6 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi
| 75,8 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703
Pixel - 72 dpi


Diagramm/Product/Travel



ID: kazm1s07

| 102,8 kB | .jpg | 352.778 x 304.8 mm - 1000 x 864
Pixel - 72 dpi
| 2,9 kB | .png | 74.083 x 63.853 mm - 210 x 181 Pixel
- 72 dpi


Graphic/Product/Contact



ID: kazm1k29

| 111,9 kB | .jpg | 352.778 x 227.894 mm - 1000 x 646
Pixel - 72 dpi


Dimension/Other



ID: 1azm1g23

| 76,8 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi

Dimension/Other



ID: 1azm1g24

| 82,4 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 202021-01-30T19:13:20+01:000701Europe/BerlinSat, 30 Jan 2021 19:13:20

+010020pmSaturday.30pm31Europe/BerlinCET1301Europe/BerlinJanuary2021Sat, 30 Jan 2021 19:13:20
+010001pm31