Product data sheet Characteristics

XCKD3918P20

XCKD compact limit switch ISO M20-

Product Life Status: END OF STANDARD SERVICE

TODAY
FEB 21, 2021

End of Commercialization
OCT 30, 2020

End of Standard Service
OCT 30, 2020



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch
Device short name	XCKD
Body type	Fixed
Material	Metal
Body material	Zamak
Head material	Zamak
Fixing mode	By the body

Product Life Status: END OF STANDARD SERVICE

FEB 21, 2021

End of Commercialization OCT 30, 2020

End of Standard Service OCT 30, 2020

Complementary

Contacts insulation form	Zb
Short-circuit protection	10 A cartridge fuse, type gG
Mechanical durability	10000000 cycles

Environment

Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27	
Vibration resistance	25 gn (f= 10500 Hz) conforming to IEC 60068-2-6	
IK degree of protection	IK06 conforming to EN 50102	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4070 °C	
Protective treatment	TC	

Packing Units

Package 1 Weight	0.211 kg	
Package 1 Height	0.340 dm	
Package 1 width	0.500 dm	
Package 1 Length	1.300 dm	