

CSS 8-180-2P+D-M-L



- Pre-wired cable 7-pole
- Thermoplastic enclosure
- Misaligned actuation possible
- Electronic contact-free, coded system
- Max. length of the sensor chain 200 m
- 2 short-circuit proof PNP safety outputs
- Self-monitoring series-wiring of 16 sensors
- High repeat accuracy of the switching points
- Early warning when operating near the limit of the sensor's hysteresis range
- Comfortable diagnostics through sensor LED and electronic signalling output

Data

Ordering data

	CSS 8-180-2P+D-M-L
	101169558
EAN (European Article Number)	4030661295992
eCl@ss number, Version 9.0	27-27-24-03

Approval - Standards

IFA
cULus
EAC

General data

	CSS 180
	IEC 61508
	IEC 60947-5-3
Active principle	inductive

Housing construction form Cylinder, thread

Installation conditions
(mechanical) not flush

Sensor topology Sensor for series wiring
Individual sensor or end sensor in a series

Enclosure material Glass-fibre, reinforced thermoplastic

Active area Glass-fibre, reinforced thermoplastic

Material of the nuts Glass-fibre, reinforced thermoplastic

Gross weight 149 g

Reaction time, maximum 30 ms

Duration of risk,
maximum 30 ms

General data - Features

Short circuit detection Yes

Short-circuit recognition Yes

Safety functions Yes

Integral System
Diagnostics, status Yes

Number of semi-
conductor outputs with
signaling function 1

Number of fail-safe
digital outputs 2

Number of Series-wiring
of sensors 16

Safety appraisal

ISO 13849-1
IEC 60947-5-3
IEC 61508

Performance level, up to e

Control category to
EN13849 4

PFH-value 2.50×10^{-9} /h

Safety Integrity Level
(SIL), applicable for 3

Mission Time 20 Year(s)

Mechanical data

Switch distance 8 mm

Ensured switch distance
"ON" S_{ao} 7 mm

Ensured switch distance
"OFF" S_{ar} 10 mm

Hysteresis (Switch distance), maximum	0.7 mm
Repeat accuracy R R	0.2 mm
Tightening torque of nuts, maximum	3 Nm

Mechanical data - Connection technique

Terminal Connector	Cable
Length of cable	2 m
Terminal connector, Input/Output	7-pole
Wire cross-section	0.3 mm ²
Wire cross-section	23 AWG

Mechanical data - Dimensions

	M18
width across flats	24 BK
Length of sensor	92 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529 IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm 30 g / 11 ms II

Ambient conditions - Insulation value

Rated impulse withstand voltage	0.8 kV III 3
---------------------------------	--------------------

Electrical data

Voltage type	DC (direct current)
--------------	---------------------

Operating voltage, minimum	20.4 VDC
Operating voltage, maximum	26.4 VDC
No-load current	50 mA
	24 VDC
Operating current	1,000 mA
Switching frequency, approx.	3 Hz

Electrical data - Fail-safe digital outputs

Rated operating current (safety outputs)	500 mA
Output current, (fail-safe output), maximum	0.5 A
Versions	p-type
Voltage drop U_d , maximum	0.5 V
Current leakage	0.5 mA
Voltage, Utilisation category DC12	24 VDC
Current, Utilisation category DC12	0.5 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.5 A

Electrical data - Diagnostic output

	24 VDC
Versions	p-type
Voltage drop U_d , maximum	4 V
Voltage, Utilisation category DC12	24 VDC
Current, Utilisation category DC12	0.1 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.1 A

Status indication

Note (LED switching conditions display)	Multi-coloured LED: Green, Red, Yellow
--	--

Pin assignment

PIN 1	A1 Ue Brown
PIN 2	X2 safety input 2: White
PIN 3	A2 GND Blue
PIN 4	Y1 Safety output 1 Black
PIN 5	signalling output: Grey
PIN 6	X2 Safety input 2 violet
PIN 7	Y2 Safety output 2 red

Scope of delivery

Included in delivery	Actuators must be ordered separately.
Delivery scope of Mounting material	2x nuts M18 x 1

Accessory

CST 180-1
CST 180-2
PROTECT PSC1
SRB-E-301ST
SRB-E-201LC

Notes

Note (General)	Evaluation requirements: dual-channel safety input, suitable for p-type sensors with NO function. The safety-monitoring module must tolerate internal functional tests of the sensors with cyclic switch-off of the sensor outputs for max. 0.25 ms. Short-circuit recognition by the evaluation is not necessary.
----------------	--

Ordering code

Product type description:

CSS 8-180-(1)-(2)-(3)

(1)

2P 2 short-circuit proof PNP safety outputs

2P+D 2 short-circuit proof PNP safety outputs and diagnostic output

(2)

E Individual sensor or end sensor in a series

Y Series-wiring

M Multifunction connection

Photo/Product/Group



ID: kcs18f19

| 176,6 kB | .jpg | 352.778 x 222.603 mm - 1000 x 631
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 532021-01-31T06:09:53+01:000601Europe/BerlinSun, 31 Jan 2021 06:09:53

+010053amSunday.31am31Europe/BerlinCET0901Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:09:53

+010001am31