XZCPV1670L5

pre-wired connectors XZ - straight female - 7/8" - 3 pins - cable PVC 5m



Main		
Accessory / separate part category	Cabling accessory	
Accessory / separate part type	Pre-wired connectors	
Series name	General purpose	

Complementary

Complementary		
Electrical connection	Straight female connector 7/8", 3 pins	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	5 m	
Cable outer diameter	5.2 mm	
Cable composition	3 x 0.75 mm²	
Wire insulation material	PVC	
[Ue] rated operational voltage	250 V AC 300 V DC	
[In] rated current	7 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	
Net weight	0.5 kg	

Environment

LITVITOTITICITE		
IP degree of protection	IP65 IP67	
Product certifications	CULus	
Ambient air temperature for operation	-2580 °C static	
Ambient air temperature for storage	-2580 °C	

Packing Units

Package 1 Weight	0.332 kg	
Package 1 Height	0.400 dm	
Package 1 width	2.600 dm	
Package 1 Length	3.200 dm	

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) E EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	€

Contractual warranty


Warranty 18 months



Product data sheet Dimensions Drawings

XZCPV1670L5

Dimensions



L: Lenght of cable

Product data sheet Connections and Schema

XZCPV1670L5

Connections and Schemes

Connectors



GN: Green RD/ Red/White

WH:

RD/ Red / Black

BK: