XZCC20FDM30B

female, 1/2 20UNF, 3-pin, straight connector - cable gland Pg 7



Main	
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Straight female connector 1/2 20 UNF, 3 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal / wire size <0.75 mm² / clamping capacity 36 mm

Complementary

1		
Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
[Ue] rated operational voltage	250 V AC	
[In] rated current	4 A	
Enclosure material	Plastic	
Minimum insulating resistance	1000 GΩ	
Contact resistance	8000 μOhm	
Net weight	0.02 kg	

Environment

2. William China		
IP degree of protection	IP67	
Ambient air temperature for operation	-4085 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	25 g	
Package 1 Height	2.5 cm	
Package 1 width	5 cm	
Package 1 Length	7 cm	
Unit Type of Package 2	S01	
Number of Units in Package 2	100	
Package 2 Weight	2.61 kg	
Package 2 Height	15 cm	
Package 2 width	15 cm	
Package 2 Length	40 cm	

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes

Contractual warranty


Warranty 18 months



Product data sheet Dimensions Drawings

XZCC20FDM30B

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Product data sheet Connections and Schema

XZCC20FDM30B

Connections and Schemes

