

T2C 452-12Y



- Metal enclosure
- Case-hardened lever
- With latching end position
- 2 cable entries M 20 x 1.5
- 118 mm x 127 mm x 64 mm (basic component)
- Actuator heads can be repositioned by 4 x 90°
- Change in actuating direction by repositioning actuator head

Data

Ordering data

	T2C 452-12Y
	101059694
EAN (European Article Number)	4030661037134
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

CCC
EAC

General data

Product name	452 fork lever 2C
	EN 60947-5-1
Active principle	mechanical
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	1,745 g

General data - Features

Number of openers	2
-------------------	---

Number of shutters	1
--------------------	---

Mechanical data

Actuating element	Fork lever
Mechanical life, minimum	10,000,000 Operations
Contact opening	2 x 6 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection
	1.5 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	222 mm
Length of sensor	64 mm
Width of sensor	118 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	16 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	4 A
Switching element	NO contact, NC contact
Note (Switching element)	with double break
Switching principle	Creep circuit element

Pictures

Photo/Product/Catalogue



ID: bt441f07

| 132,2 kB | .jpg | 211.314 x 211.314 mm - 599 x 599

Pixel - 72 dpi

| 21,7 kB | .png | 74.083 x 74.083 mm - 210 x 210

Pixel - 72 dpi

Photo/Product/Catalogue



ID: kt452f01


| 56,2 kB | .png | 74.083 x 112.536 mm - 210 x 319

Pixel - 72 dpi

| 673,8 kB | .jpg | 352.778 x 536.575 mm - 1000 x

1521 Pixel - 72 dpi

Dimension/Product/Basic



ID: 1t452g01


| 176,9 kB | .jpg | 352.778 x 303.389 mm - 1000 x 860

Pixel - 72 dpi

| 5,8 kB | .png | 74.083 x 63.853 mm - 210 x 181 Pixel
- 72 dpi

| 35,1 kB | .cdr |

Dimension/Product/Actuator



ID: 1t422b06

| 107,8 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701


Pixel - 72 dpi

| 9,7 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi

Illustration/Product/Function



ID: 235hz01



| 229,3 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124
Pixel - 72 dpi

| 4,0 kB | .png | 74.083 x 157.339 mm - 210 x 446
Pixel - 72 dpi

| 15,6 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 552021-01-31T15:59:55+01:000301Europe/BerlinSun, 31 Jan 2021 15:59:55

+010055pmSunday.31pm31Europe/BerlinCET5901Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:59:55

+010001pm31