



**HIGH TEMPERATURE GLASS OPTICAL FIBRES**

- Models with flexible fibre heads (with sleeve)
- Wide range of accessories (AF serie)
- IP67 protection degree
- SSF - FS1 - FX3 - FX4 serie connectable
- Approvals: CE

**Detection properties**

|                          |     |
|--------------------------|-----|
| Nominal sensing distance | n/a |
| Sensitivity adjustment   | n/a |

**Application**

|             |                          |
|-------------|--------------------------|
| Description | Straight female shielded |
| Functions   | Cable/connector          |

**Outputs**

|               |     |
|---------------|-----|
| Output type   | n/a |
| Response time | n/a |

**Electrical data**

|                   |           |
|-------------------|-----------|
| Operating Voltage | 10-30 VDC |
| Emission          | n/a       |

**Mechanical data**

|             |             |
|-------------|-------------|
| Dimensions  | L=10m       |
| Connections | M12 3-poles |
| Material    | PVC (Grey)  |

**Generical Data**

|            |       |
|------------|-------|
| Dimensions | L=10m |
|------------|-------|

---

---

**Datasensing S.r.l.**

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail [info@datasensing.com](mailto:info@datasensing.com)

**date of printing**

29/04/2022 11:50:09