

Technical data sheet

Safety relay

Part no.: 50133023

MSI-SR-ES31-03

Contents

- Technical data
- Dimensioned drawings
- Electrical connection
- Circuit diagrams
- Notes



Figure can vary



Technical data

Basic data

Series	MSI-SR-ES31
Application	Base device for E-Stop applications

Functions

Functions	Monitoring of E-Stop circuits
	Monitoring of position switches
	Monitoring of proximity switches
Restart	Automatic
	Manual

Characteristic parameters

SIL	2, IEC 61508
SILCL	2, IEC/EN 62061
Performance Level (PL)	d, EN ISO 13849-1
MTTF _d	73 years, EN ISO 13849-1
Mission time T _M	20 years, EN ISO 13849-1
Category	3, EN ISO 13849
B10 _d at DC13 (inductive load)	300,000 number of cycles, (5 A, 230 V), 700,000 (1 A, 230 V)
B10 _d at AC15 (inductive load)	200,000 number of cycles, (5 A, 230 V), 380,000 (1 A, 230 V)

Electrical data

Supply circuit	
Nominal voltage U _N	24 V AC/DC
Nominal frequency	50 ... 60 Hz
Operating voltage	0.85 ... 1.1 x U _N
Rated power DC	1.3 W
Galvanic isolation between supply and control circuit	Yes (when U _N ≥ AC 115-120 V, AC 230 V)
Output circuit	
Number of outputs, safety-oriented, undelayed, contact-based	3 Piece(s)
Number of outputs, signaling function, undelayed, contact-based	1 Piece(s)
Release current paths	NO
Signaling current paths	NC
Contact material	Ag alloy, gold-plated
Usage category AC-15 (NO contact)	Ue 230V, Ie 5A
Usage category DC-13 (NO contact)	Ue 24V, Ie 5A
Short circuit protection (NO contact)	gG class safety fuse 6A, melting integral
Nominal switching voltage, release current paths AC	230 V
Nominal switching voltage, signaling current paths AC	230 V
Max. thermal continuous current I _{th} , release current paths	8 A
Max. thermal continuous current I _{th} , signaling current paths	5 A
Max. total current I ² of all current paths	9 A ²
Mechanical life time	100,000,000 switching cycles

Control circuit

Evaluation of the inputs	one- or two-channel
Nominal output voltage DC	24 V
Input current at the control inputs (safety circuit/reset circuit)	90 mA
Max. peak current at the control inputs (safety circuit/reset circuit)	1,500 mA
Max. cable resistance, per channel	≤ (5 + (1.333 x U _B / U _N - 1) x 200) Ω
Minimum switch-on time	60 ms
Response time (automatic start t _{A2})	60 ms
Release time t _R	60 ms
Recovery time t _w	200 ms

Connection

Number of connections	1 Piece(s)
Connection 1	
Function	Signal IN
	Signal OUT
	Voltage supply
Type of connection	Terminal
Type of terminal	Spring-cage terminal
No. of pins	15 -pin

Cable properties

Connection cross sections	2 x 0.2 to 1.5 mm ² , wire
	2 x 0.2 to 1.5 mm ² , wire
	2 x 0.25 to 1.5 mm ² , wire with wire-end sleeve

Mechanical data

Dimension (W x H x L)	22.5 mm x 106.5 mm x 114 mm
Net weight	200 g
Housing color	Gray
Type of fastening	Snap-on mounting

Certifications


Certifications	c UL US
	TÜV Rheinland

Classification

Customs tariff number	85364900
eCl@ss 8.0	27371819
eCl@ss 9.0	27371819
ETIM 5.0	EC001449
ETIM 6.0	EC001449

Dimensioned drawings

All dimensions in millimeters



Electrical connection

Connection 1

Function	Signal IN
	Signal OUT
	Voltage supply
Type of connection	Terminal
Type of terminal	Spring-cage terminal
No. of pins	15 -pin


Pin Pin assignment

	13
1	Release current path 1 (NO contact)
	14
2	Release current path 1 (NO contact)
	23

Electrical connection

Pin	Pin assignment
3	Release current path 2 (NO contact) 24
4	Release current path 2 (NO contact) 33
5	Release current path 3 (NO contact) 34
6	Release current path 3 (NO contact) 41
7	Signaling current path (NC contact) 42
8	Signaling current path (NC contact) A1
9	+24V A1
10	+24V A2
11	GND A2
12	GND Y1
13	Control circuit of reset button Y2
14	Control circuit of reset button (automatic reset) Y3
15	Control circuit of reset button (manual reset)

Circuit diagrams



Notes

 Observe intended use!	
	⌚ The product may only be put into operation by competent persons. ⌚ Only use the product in accordance with its intended use.