



UV8H 433Y

- 3 Contacts
- Metal enclosure
- 3 cable entries M 20 x 1.5
- Lever can be transposed by 180°
- 62 mm x 105 mm x 50 mm (basic component)
- Continuous adjustment of lever position 360°
- Switching points and contact function adjustable
- Actuator head can be repositioned in steps 4 x 90°

Data

Ordering data

	UV8H 433Y
	101060588
EAN (European Article Number)	4030661047690
eCI@ss number, Version 9.0	27-27-06-01

Approval - Standards

EAC

General data

Product name	U 433 roller lever 8H EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	516 g

General data - Features

Number of openers	3
-------------------	---

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 1.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 1.5 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	156 mm
Length of sensor	50 mm
Width of sensor	62 mm
Width of Castor	8.5 mm
Diameter of Castor	20 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Electrical data

Thermal test current	16 A
Switching element	Opener (NC)
Switching principle	Creep circuit element

Notes

Note (General)	Type of contact and switching points can be factory set to order.
----------------	---

Ordering code

Product type description:

U(1) 433Y-(2)-(3)

(1)

S Plunger S

K Offset roller lever K

8H Roller lever 8H

H Roller lever H

3H Roller lever 3H

7H Roller lever 7H

4H Spring rod lever on shaft 4H

9H Rod lever 9H

10H Rod lever 10H

2H Leaf spring lever 2H

6H Leaf spring lever 6H

(2)

without 3 NC contact

1S/2OE 1 NO contact/2 NC contacts

2S/1OE 2 NO contacts/1 NC contact

(3)

1272 Version for low temperatures to -30 °C

Pictures

Photo/Product/Catalogue



ID: ku43hf26


| 486,5 kB | .jpg | 155.575 x 303.389 mm - 441 x 860

Pixel - 72 dpi

| 129,7 kB | .png | 74.083 x 144.286 mm - 210 x 409

Pixel - 72 dpi

Dimension/Product/Basic



ID: 1u43-g03

| 87,9 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703 Pixel - 72 dpi
| 28,0 kB | .cdr |
| 4,1 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel - 72 dpi


Diagramm/Product/Travel



ID: ku43-s03

| 93,9 kB | .jpg | 352.778 x 182.386 mm - 1000 x 517
Pixel - 72 dpi
| 1,2 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel
- 72 dpi


Graphic/Product/Contact



ID: k3o--k02

| 65,3 kB | .jpg | 352.778 x 292.806 mm - 1000 x 830
Pixel - 72 dpi
| 18,7 kB | .cdr |

Illustration/Product/Function



ID: ku432a01

| 19,8 kB | .png | 74.083 x 49.742 mm - 210 x 141
Pixel - 72 dpi
| 203,1 kB | .cdr |
| 157,4 kB | .jpg | 352.778 x 236.361 mm - 1000 x 670
Pixel - 72 dpi

Illustration/Product/Function



ID: 235hz05

| 15,2 kB | .cdr |


| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124

Pixel - 72 dpi

| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446

Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t15vb02

| 89,6 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

| 4,2 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 282021-01-31T15:35:28+01:000301Europe/BerlinSun, 31 Jan 2021 15:35:28

+010028pmSunday.31pm31Europe/BerlinCET3501Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:35:28

+010001pm31