

## BNS 36-11/01ZG-R



- Long life
- no mechanical wear
- 88 mm x 25 mm x 13 mm
- Insensitive to soiling
- Thermoplastic enclosure
- Concealed mounting possible
- Insensitive to transverse misalignment

### Data

#### Ordering data

BNS 36-11/01ZG-R

101193177

EAN (European Article Number) 4030661359878

eCl@ss number, Version 9.0 27-27-24-02

#### Approval - Standards

TÜV  
cULus  
EAC

#### General data

BNS 36

IEC 60947-5-3

BG-GS-ET-14

Installation conditions  
(mechanical)

quasi-flush

Enclosure material

Glass-fibre, reinforced thermoplastic

Gross weight

71 g

#### General data - Features

Coding

Yes

Integral System Diagnostics,  
status

Yes

Number of openers

2

Number of shutters

1

|                           |   |
|---------------------------|---|
| Number of safety contacts | 2 |
| Number of cable wires     | 6 |

### Safety appraisal

|              |             |
|--------------|-------------|
|              | ISO 13849-1 |
| Mission Time | 20 Year(s)  |

### Safety appraisal - Safety outputs

B10d- Value Normally-closed  
 contact/Normally open contact 25,000,000 Operations  
 (NC/NO)

### Mechanical data

|                                 |                                                                                                                                                                                                                                                                                |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Actuating element               | Magnet                                                                                                                                                                                                                                                                         |
| Door hinge                      | Right                                                                                                                                                                                                                                                                          |
| Ensured switch distance "ON" S  | 7 mm                                                                                                                                                                                                                                                                           |
| ao                              |                                                                                                                                                                                                                                                                                |
| Ensured switch distance "OFF" S | 17 mm                                                                                                                                                                                                                                                                          |
| ar                              |                                                                                                                                                                                                                                                                                |
| Notice (Switch distance Sn)     | Axial misalignment, a horizontal and vertical misalignment of the safety sensor and the actuator are tolerated. The possible misalignment depends on the distance of the active surfaces of the sensor and the actuator. The sensor remains active within the tolerance range. |
| Direction of motion             | Head-on to the active surface                                                                                                                                                                                                                                                  |

### Mechanical data - Connection technique

|                    |                     |
|--------------------|---------------------|
| Terminal Connector | Cable               |
| Length of cable    | 1 m                 |
| Wire cross-section | 0.3 mm <sup>2</sup> |
| Wire cross-section | 30 AWG              |
|                    | PVC                 |

### Mechanical data - Dimensions

|                  |       |
|------------------|-------|
| Height of sensor | 25 mm |
| Length of sensor | 13 mm |
| Width of sensor  | 88 mm |

### Ambient conditions

|                                            |        |
|--------------------------------------------|--------|
|                                            | IP67   |
| Ambient temperature, minimum               | -25 °C |
| Ambient temperature, maximum               | +70 °C |
| Storage and transport temperature, minimum | -25 °C |

|                                            |                                              |
|--------------------------------------------|----------------------------------------------|
| Storage and transport temperature, maximum | +70 °C                                       |
| Resistance to vibrations to EN 60068-2-6   | 10 ... 55 Hz, amplitude 1 mm<br>30 g / 11 ms |

### Electrical data

|                              |                     |
|------------------------------|---------------------|
| Voltage type                 | DC (direct current) |
| Switching voltage, maximum   | 24 VDC              |
| Switching current, maximum   | 0 A                 |
| Switching capacity, maximum  | 0.2 W               |
| Switching frequency, maximum | 5 Hz                |

### Status indication

|                                             |                                                  |
|---------------------------------------------|--------------------------------------------------|
| Note (Integral System Diagnostics, status ) | The LED is illuminated when the guard is closed. |
|---------------------------------------------|--------------------------------------------------|

### Scope of delivery

|                      |                                       |
|----------------------|---------------------------------------|
| Included in delivery | Actuators must be ordered separately. |
|----------------------|---------------------------------------|

### Accessory

BPS 36-2  
SRB-E-301ST  
SRB-E-201LC

### Notes

|                |                                                                                                                                                 |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Note (General) | Contact symbols shown for the closed condition of the guard device.<br>The contact configuration for versions with or without LED is identical. |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------|

### Ordering code

Product type description:

BNS 36-(1)(2)Z(3)-(4)-(5)

(1)

**11** 1 NO contacts/1 NC contact

**02** 2 NC contact

(2)

**without** with diagnostic output

**/01** 1 NC contact

(3)

**without** without LED switching conditions display

**G** with LED switching conditions display

(4)

**without** Pre-wired cable

**ST** with connector

(5)

**L** Door hinge on left-hand side

**R** Door hinge on right-hand side

## Pictures

### Photo/Product/Catalogue




ID: kbns3f35

| 16,0 kB | .png | 74.083 x 19.403 mm - 210 x 55 Pixel  
- 72 dpi

| 205,0 kB | .jpg | 352.778 x 92.428 mm - 1000 x 262  
Pixel - 72 dpi

### Dimension/Product/Basic




ID: 1bns3g13

| 62,4 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695  
Pixel - 72 dpi

| 3,2 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel  
- 72 dpi

| 25,5 kB | .cdr |

### Graphic/Product/Contact




ID: kbns2k04

| 19,5 kB | .cdr |

| 87,7 kB | .jpg | 352.778 x 85.372 mm - 1000 x 242  
Pixel - 72 dpi

### Diagramm/Product/Curve



ID: kbns3a29

| 110,2 kB | .png | 50.038 x 30.649 mm - 591 x 362

Pixel - 300 dpi


| 165,7 kB | .jpg | 352.778 x 215.9 mm - 1000 x 612

Pixel - 72 dpi

| 165,7 kB | .jpg | 352.778 x 215.9 mm - 1000 x 612

Pixel - 72 dpi

### Diagramm/Product/Curve



ID: kbns3a30

| 41,1 kB | .cdr |


| 164,2 kB | .jpg | 352.778 x 215.547 mm - 1000 x 611

Pixel - 72 dpi

| 16,9 kB | .png | 74.083 x 45.156 mm - 210 x 128

Pixel - 72 dpi

### Illustration/Product/Function



ID: kbn36c01

| 1,8 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel  
- 72 dpi

| 52,3 kB | .jpg | 352.778 x 250.825 mm - 1000 x 711

Pixel - 72 dpi

| 20,2 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 142021-01-31T06:30:14+01:000601Europe/BerlinSun, 31 Jan 2021 06:30:14

+010014amSunday.31am31Europe/BerlinCET3001Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:30:14

+010001am31