



TV1H 255-20Z

- Metal enclosure
- 63 mm x 63,5 mm x 30 mm
- 3 cable entries M 20 x 1.5
- Mounting details to EN 50047
- Wide range of alternative actuators
- Lever angle adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

TV1H 255-20Z

101174949

eCl@ss number, Version 9.0

27-27-06-01

General data

Product name	T 255 roller lever 1H IEC 60947-5-1 ISO 13849-1 BG-GS-ET-15
Housing construction form	Norm construction design
Actuator type to DIN EN 50047	A
Enclosure material	Zink
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Lever material	Plastic
Roller material	Plastic

General data - Features

Number of auxiliary contacts	2
------------------------------	---

Safety appraisal

ISO 13849-1

Mission Time	20 Year(s)
--------------	------------

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	20,000,000 Operations
Actuating speed, minimum	492 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note Bounce duration	Bounce duration in accordance with actuating speed
Note (Switchover time)	Switchover time in accordance with actuating speed
Actuating torque, minimum	0.2 Nm
Positive break torque	0.2 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection 0.75 mm² 2.5 mm²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	110.5 mm
Length of sensor	42.5 mm
Width of sensor	63 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	Normally open contact (NO)

Switching principle
Switching frequency

Creep circuit element
5,000 /h

Notes

Note (General)

Switch with 2 NO contacts are not for security tasks

Ordering code

Product type description:

(1)(2) 2(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

4S Plunger 4S

4R Roller plunger 4R

1R Offset roller lever 1R

K Offset roller lever K

3K Angle roller lever 3K

4K Angle roller lever 4K

K4 Angle roller lever K4

1H Roller lever 1H

7H Roller lever 7H

10H Rod lever 10H

12H Roller lever 12H

14H Roller lever 14H

AF Spring rod lever AF

RMS Brass roller

(3)

3 slim design

5 large design

(4)

02 2 NC contact

11 1 NO contacts/1 NC contact

20 2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)

(5)

- H** Slow action with staggered contacts
- UE** Slow action with overlapping contacts


- (6)
 - without** Cable entry M20
 - ID** IDC method of termination
 - NPT** Cable entry NPT 1/2"
 - ST** M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)
 - ST-2310** M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)


- (7)
 - 2574** Enclosure with L-shaped mounting holes (horizontally or vertically adjustable)

- (8)
 - 2138** Roller lever 7H for position switches with safety function

- (9)
 - 1637** Gold-plated contacts

Pictures


Photo/Product/Catalogue	
	ID: k255hf01 71,8 kB .png 73.731 x 114.3 mm - 209 x 324 Pixel - 72 dpi 908,8 kB .jpg 338.667 x 523.875 mm - 960 x 1485 Pixel - 72 dpi
Diagramm/Product/Travel	
	ID: kh235s04 1,6 kB .png 74.083 x 22.931 mm - 210 x 65 Pixel - 72 dpi 49,0 kB .jpg 352.778 x 109.714 mm - 1000 x 311 Pixel - 72 dpi 24,5 kB .cdr
Graphic/Product/Contact	



ID: k--2sk01

| 51,9 kB | .jpg | 352.778 x 135.819 mm - 1000 x 385
Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1h236g01

| 87,7 kB | .cdr |
| 7,8 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi
| 85,2 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 392021-01-31T04:02:39+01:000401Europe/BerlinSun, 31 Jan 2021 04:02:39

+010039amSunday.31am31Europe/BerlinCET0201Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:02:39

+010001am31