



UVH 432Y

- 2 Contacts
- Metal enclosure
- 3 cable entries M 20 x 1.5
- Lever can be transposed by 180°
- 62 mm x 80 mm x 50 mm (basic component)
- Continuous adjustment of lever position 360°
- Switching points and contact function adjustable
- Actuator head can be repositioned in steps 4 x 90°

Data

Ordering data

	UVH 432Y
	101161093
EAN (European Article Number)	4030661192178
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

EAC

General data

Product name	U 432 roller lever H
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	420 g

General data - Features

Number of openers	2
-------------------	---

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 2,000,000 Operations

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 1.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 1.5 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	138 mm
Length of sensor	50 mm
Width of sensor	62 mm
Width of Castor	8.5 mm
Diameter of Castor	20 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Electrical data

Thermal test current	16 A
Switching element	Opener (NC)
Switching principle	Creep circuit element

Notes

Note (General) Type of contact and switching points can be factory set to order.

Ordering code

Product type description:

U(1) 432Y-(2)-(3)

(1)

S Plunger S

K Offset roller lever K

8H Roller lever 8H

H Roller lever H

3H Roller lever 3H

7H Roller lever 7H

4H Spring rod lever on shaft 4H

9H Rod lever 9H

10H Rod lever 10H

2H Leaf spring lever 2H

6H Leaf spring lever 6H

without 2 NC contact

25 2 NO contacts

1S/1OE 1 NO contacts/1 NC contact

(3)

1272 Version for low temperatures to -30 °C

Pictures

Photo/Product/Catalogue



ID: ku43hf01

| 451,3 kB | .jpg | 161.572 x 272.344 mm - 458 x 772


Pixel - 72 dpi

| 111,8 kB | .png | 73.731 x 124.531 mm - 209 x 353

Pixel - 72 dpi

Dimension/Product/Basic

ID: 1u43-g02



| 82,9 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi
| 3,7 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi
| 27,7 kB | .cdr |


Diagramm/Product/Travel

ID: ku43-s03



| 93,9 kB | .jpg | 352.778 x 182.386 mm - 1000 x 517 Pixel - 72 dpi
| 1,2 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel - 72 dpi


Graphic/Product/Contact



ID: k2o1sk02

| 18,4 kB | .cdr |
| 82,3 kB | .jpg | 352.778 x 193.322 mm - 1000 x 548 Pixel - 72 dpi

Illustration/Product/Function



ID: ku432a01

| 19,8 kB | .png | 74.083 x 49.742 mm - 210 x 141 Pixel - 72 dpi
| 203,1 kB | .cdr |
| 157,4 kB | .jpg | 352.778 x 236.361 mm - 1000 x 670 Pixel - 72 dpi


Illustration/Product/Function



ID: 235hz05

| 15,2 kB | .cdr |
| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124 Pixel - 72 dpi
| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t15vb01

| 10,3 kB | .png | 74.083 x 51.858 mm - 210 x 147

Pixel - 72 dpi

| 114,5 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 222021-01-31T15:31:22+01:000301Europe/BerlinSun, 31 Jan 2021 15:31:22

+010022pmSunday.31pm31Europe/BerlinCET3101Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:31:22

+010001pm31