

TS 064-12Y

- Metal enclosure
- 3 or 4 Contacts
- 2 cable entries M 25 x 1.5
- 184 mm x 111 mm x 149 mm (basic component)
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

TS 064-12Y

101057473

EAN (European Article Number) 4030661253152

eCl@ss number, Version 9.0 27-27-06-01

Approval - Standards

cULus

CCC

EAC

General data

Product name	064 plunger S
	EN 60947-5-1
Active principle	mechanical
Slide form	Sphere
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	3,240 g

General data - Features

Number of openers	2
Number of shutters	1

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 2,000,000 Operations

Mechanical data

Actuating element	Plunger
Mechanical life, minimum	1,000,000 Operations
Actuating angle	20 °
Contact opening	2 x 4 mm
Actuating speed, minimum	600 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 1.5 mm ² 4 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	11 AWG

Mechanical data - Dimensions

Height of sensor	111 mm
Length of sensor	149 mm
Width of sensor	156 mm
Diameter of the Plunger	10 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	25 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	25 A

Switching element	NO contact / NC contact
Note (Switching element)	with double break
Switching principle	Creep circuit element
Switching frequency	1,000 /h

Notes

Note (General)	Actuation from the side of the plunger should be avoided, since this reduces the mechanical life of the position switch.
----------------	--

Ordering code

Product type description:

T(1) 064-(2)Y-(3)

(1)

S Plunger S

J Offset roller lever J

X Offset roller lever X

(2)

03 3 NC contact

12 1 NO contact/2 NC contacts

21 2 NO contacts/1 NC contact

30 3 NO contacts

04 4 NC contact

13 1 NO contacts/3 NC contact

22 2 NO contacts/2 NC contact

31 3 NO contacts/1 NC contact

40 4 NO contacts

(3)


UE Slow action with overlapping contacts

H Slow action with staggered contacts

R Latching 2 x 45°

Pictures

Photo/Product/Catalogue



ID: kt-64f01


| 30,6 kB | .png | 74.083 x 59.267 mm - 210 x 168

Pixel - 72 dpi

| 460,9 kB | .jpg | 352.778 x 282.575 mm - 1000 x 801

Pixel - 72 dpi

Dimension/Product/Basic



ID: 1t-64g01


| 8,9 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi

| 103,5 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

| 33,2 kB | .cdr |

Graphic/Product/Contact




ID: k2o1sk03

| 62,3 kB | .jpg | 352.778 x 266.347 mm - 1000 x 755

Pixel - 72 dpi

| 23,8 kB | .cdr |

Dimension/Product/Actuator



ID: 1tm-sb01

| 2,0 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 38,3 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691

Pixel - 72 dpi

Illistration/Product/Function



ID: 235sz01

| 14,1 kB | .cdr |

| 1,8 kB | .png | 74.083 x 251.883 mm - 210 x 714

Pixel - 72 dpi

| 95,3 kB | .jpg | 352.778 x 1199.444 mm - 1000 x

3400 Pixel - 72 dpi



K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 402021-01-31T16:08:40+01:00401Europe/BerlinSun, 31 Jan 2021 16:08:40

+010040pmSunday.31pm31Europe/BerlinCET0801Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:08:40

+010001pm31