



T3Z 068-22YRS

- Robust design
- Metal enclosure
- Low actuating force
- 2 switches in one enclosure
- two-side operation / wire up to 2 x 50 m long

Data

Ordering data

	T3Z 068-22yrs
	101087882
EAN (European Article Number)	4030661057217
eCl@ss number, Version 9.0	27-37-12-01

Approval - Standards

cULus
cCSAus
CCC
EAC

General data

	T3Z 068
	IEC 60947-5-1
	IEC 60947-5-5
	ISO 13850
Enclosure material	Grey cast iron, painted
Material of the contacts, electrical	Silver
Material of the cover	Grey cast iron, painted
Length of the wire, maximum	50 m
Gross weight	4,825 g

General data - Features

Key reset	Yes
Number of auxiliary contacts	2

Number of safety contacts	2
---------------------------	---

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	100,000 Operations
-----------------------------------	--------------------

Mechanical data

Actuating element	Roller lever N300
Mechanical life, minimum	50,000 Operations
Positive break angle	32 °
Actuating force, maximum	50 N
Note (Actuating force)	30 N in wire direction
Actuation direction	Each time 75° right-hand side and left-hand side rotation
Positive break force, minimum	50 N
Positive break torque	0.2 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection
	0.75 mm ²
	1.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	2.5 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	6 A
Switching element	NO contact, NC contact
Switching principle	Creep circuit element

Notes

Note (General) At 3 m distance intermediate wire supports are required, see accessories

Ordering code

Product type description:

T3Z 068-(1)YR(2)(3)

(1)

11 1 NO contacts/1 NC contact

22 2 NO contacts/2 NC contact

33 3 NO contacts / 3 NC contacts (not combinable in combination with -2909)

(2)

without Reset by pull ring

S Key reset (not combinable in combination with -2909)

(3)

without without indicator lamp

G with indicator lamp (not combinable in combination with -2909)

2909 Outside parts in stainless steel

Pictures

Photo/Product/Catalogue



ID: kt3z0f03

| 55,7 kB | .png | 73.731 x 100.542 mm - 209 x 285



Pixel - 72 dpi

| 781,6 kB | .jpg | 352.778 x 480.131 mm - 1000 x

1361 Pixel - 72 dpi

Dimension/Product/Basic

| 9,9 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi



+010001am31