



SRB-E-301ST

- **STOP 0 Function**
- **3 safety contacts**
- **1 Auxiliary contact**
- **1 oder 2-channel control**
- **Start button / Auto-start**

Data

Ordering data

	SRB-E-301ST
	103007672
EAN (European Article Number)	4030661478470
eCl@ss number, Version 9.0	27-37-18-19

Approval - Standards

TÜV
cULus
CCC
EAC

General data

	SRB-E-301ST
	IEC 61508
	ISO 13849-1
	EN 60947-5-1
	IEC 62061
	IEC 60204-1
	EN 60068-2-78
Enclosure material	Glass-fibre reinforced thermoplastic, ventilated
Material of the contacts, electrical	Ag-Ni, self-cleaning, positive drive
Gross weight	175 g

General data - Features

Stop-Category	0
Electronic Fuse	Yes
Wire breakage detection	Yes
Short-circuit recognition	Yes
Removable Terminals	Yes
Start input	Yes
Feedback circuit	Yes
Automatic reset function	Yes
Reset edge detection	Yes
Earth connection detection	Yes
Integral System Diagnostics, status	Yes
Integral System Diagnostics, error code	Yes
Number of auxiliary contacts	1
Number of LEDs	5
Number of openers	2
Number of shutters	1
Number of Safety contacts, STOP 0	3

Safety appraisal

ISO 13849-1
IEC 62061
IEC 61508

Safety appraisal - Relay outputs

Performance Level, up to	e
Control category to EN13849	4
Diagnostic Coverage (DC) Level	> 99 %
PFH-value	1.25×10^{-8} /h
PFD value	5.30×10^{-5}
Safety Integrity Level (SIL), applicable for	3
Mission time	20 Year(s)
Common Cause Failure (CCF), minimum	65

Mechanical data

Mounting	Snaps onto standard DIN rail to EN 60715
Mechanical life, minimum	10,000,000 Operations

Mechanical data - Connection technique

Terminal Connector	Screw connection, plug-in rigid or flexible
--------------------	--

Terminal designations	IEC/EN 60947-1
	0.25 mm ²
	2.5 mm ²
Tightening torque of Clips	0.5 Nm

Mechanical data - Dimensions

Width	22.5 mm
Height	98 mm
Depth	115 mm

Ambient conditions

	IP40
	IP54
	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-40 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, Amplitude 0.35 mm
	30 g / 11 ms

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
	III
	2

Electrical data

Frequency range	60 Hz
	24 VAC -15% / +20%
Rated AC voltage for controls, 50 Hz, minimum	20.4 VAC
Rated control voltage at AC 50 Hz, maximum	26.4 VAC
Rated AC voltage for controls, 60 Hz, minimum	20.4 VAC
Rated control voltage at AC 60 Hz, maximum	26.4 VAC
Rated AC voltage for controls at DC minimum	20.4 VDC
Rated control voltage at DC, maximum	28.8 VDC
Electrical power consumption	2.4 W
Electrical power consumption	7 VA
Contact resistance, maximum	0.1 Ω
Note (Contact resistance)	in new state
Drop-out delay in case of power failure, typically	10 ms
Drop-out delay in case of emergency, typically	10 ms
Pull-in delay at automatic start, maximum, typically	150 ms

Pull-in delay at RESET, typically	150 ms
Switching frequency, maximum	0.3 Hz

Electrical data - Safe relay outputs

Voltage, Utilisation category AC15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	4 A
Switching capacity, minimum	10 VDC
Switching capacity, minimum	10 mA
Switching capacity, maximum	250 VAC
Switching capacity, maximum	6 A

Electrical data - Digital inputs

Conduction resistance, maximum	40 Ω
--------------------------------	------

Electrical data - Relay outputs (auxiliary contacts)

Switching capacity, maximum	24 VDC
Switching capacity, maximum	1 A

Electrical data - Electromagnetic compatibility (EMC)

EMC rating	EMC-Directive
------------	---------------

Status indication

Indicated operating states	Internal operating voltage U _i Baustein-Status Fault codes
----------------------------	---

Other data

Note (applications)	Safety sensor Guard system hinged safety guard Emergency-Stop button Pull-wire emergency stop switches Safety light curtain Safety light barriers
---------------------	---

Pictures

Photo/Product/Catalogue



ID: ksrb3f27

| 122,2 kB | .png | 74.083 x 172.156 mm - 210 x 488

Pixel - 72 dpi

| 1,0 MB | .jpg | 281.869 x 655.814 mm - 799 x 1859

Pixel - 72 dpi

Graphic/Product/Wiring



ID: ksrbel02

| 116,1 kB | .jpg | 352.778 x 294.569 mm - 1000 x 835

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 372021-01-31T12:33:37+01:001201Europe/BerlinSun, 31 Jan 2021 12:33:37

+010037pmSunday.31pm31Europe/BerlinCET3301Europe/BerlinJanuary2021Sun, 31 Jan 2021 12:33:37

+010001pm31