



IFL 4-120M-01P

- DC 3-wire
- Design M12
- miniature body
- Double-insulated
- Thermoplastic enclosure

Data

Ordering data

	IFL 4-120M-01P
	101097203
EAN (European Article Number)	4030661086743
eCl@ss number, Version 9.0	27-27-01-01

General data

	IFL - M 12
	IEC/EN 60947-5-2
	DIN VDE 0660-208
Housing construction form	Cylinder, thread
Installation conditions (mechanical)	not flush
Enclosure material	Plastic
Active area	Plastic
Material of the nuts	Plastic
Material of the washer	Perbunan [®]
Gross weight	70 g

General data - Features

Integral System Diagnostics, status	Yes
Number of cable wires	3

Mechanical data

Switch distance	4 mm
Tightening torque of nuts, maximum	0.9 Nm

Mechanical data - Connection technique

Terminal Connector	Cable
Length of cable	2 m
Wire cross-section	0.1 mm ²
	PVC

Mechanical data - Dimensions

	M12
width across flats	17 BK
Length of sensor	32.6 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
	II

Electrical data

Voltage type	DC (direct current)
Operating voltage, minimum	10 V
Operating voltage, maximum	30 V
No-load current	3 mA
Operating current	200 mA
Switching element	Opener (NC)
	inductive interference protection
Protection circuit integrated	Protection against polarity reversal
	Surge protection
	Max. fuse rating
Switching frequency, approx.	1,000 Hz

Electrical data - Digital Output

Voltage drop U_d , maximum	1.2 V
Current at Voltage drop U_d	0.2 A
Versions	p-type

Status indication

Note (Integral System Diagnostics, status)	yellow LED
---	------------

Ordering code

Product type description:

IFL (1)-(2)(3)-(4)(5)(6)(7)(8)-(9)

(1)

2 Switching distance 2 mm

4 Switching distance 4 mm

NB, MBN, BN Quasi-embeddable

(2)

12 Cylinder, thread M12, metal

120 Cylinder, thread M12, plastic

(3)

without Standard body

M Miniature body

L Long design

(4)

01 Opener (NC)

10 Normally open contact (NO)

10/01 NO contact / NC contact with wiring compartment

11 1 NO contact / 1 NC contact antivalent

(5)

without Cable

ST Male connector

T Conductor with strain relief

(6)

without Standard connector version

2 Alternative connector
version

(7)

N n-type

P p-type

(8)

K Max. fuse rating

1 pulsed

(9)

2033 Stainless steel enclosure

Pictures

Photo/Product/Catalogue




ID: kifl4f08

| 13,0 kB | .png | 74.083 x 111.125 mm - 210 x 315
Pixel - 72 dpi

| 169,2 kB | .jpg | 352.778 x 529.167 mm - 1000 x
1500 Pixel - 72 dpi

Dimension/Product/Basic




ID: lifl4g11

| 74,0 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693
Pixel - 72 dpi

| 3,4 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 21,0 kB | .cdr |

Graphic/Product/Contact



ID: id3lk06

| 32,0 kB | .cdr |

| 48,5 kB | .jpg | 352.778 x 146.756 mm - 1000 x 416
Pixel - 72 dpi