



IFL15-30-01T

- AC 2-wire
- Design M30
- Metal enclosure
- Double-insulated

Data

Ordering data

	IFL 15-30-01T
	101141545
EAN (European Article Number)	4030661122458
eCl@ss number, Version 9.0	27-27-01-01

Approval - Standards

CCC

General data

	IFL - M30
	IEC/EN 60947-5-2
	DIN VDE 0660-208
Housing construction form	Cylinder, thread
Installation conditions (mechanical)	not flush
Enclosure material	Brass
Enclosure coating material	nickel-plated
Active area	Plastic
Material of the nuts	Brass
Gross weight	200 g

General data - Features

Integral System Diagnostics, status	Yes
Cable sleeve	Yes
Number of cable wires	2

Mechanical data

Switch distance	15 mm
Tightening torque of nuts, maximum	30 Nm

Mechanical data - Connection technique

Terminal Connector	Cable H03VV-F
Length of cable	2 m
Wire cross-section	0.5 mm ² PVC

Mechanical data - Dimensions

	M30
width across flats	36 BK
Length of sensor	100 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
	II

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Voltage type	AC (alternating current)
Rated supply frequency, minimum	45 Hz
Rated supply frequency, maximum	65 Hz
Operating voltage, minimum	15 V
Operating voltage, maximum	250 V
Operating current, minimum	10 mA
Operating current	500 mA
Switching element	Opener (NC)
Protection circuit integrated	inductive interference protection
Switching frequency, approx.	10 Hz

Electrical data - Digital Output

Voltage drop U_d , maximum	4.5 V
Current at Voltage drop U_d	0.2 A
Versions	Two-wire

Status indication

Note (Integral System Diagnostics, status) yellow LED

Notes

Note (General) Instead of nuts, a mounting clamp can be provided.

Ordering code

Product type description:

IFL (1)-(2)(3)-(4)(5)(6)(7)-(8)

(1)

10 Switching distance 10 mm

15 Switching distance 15 mm

(2)

30 Cylinder, thread M30, metal

300 Cylinder, thread M30, plastic

(3)

without Standard body

M Miniature body

L Long design

(4)

01 Opener (NC)

10 Normally open contact (NO)

10/01 NO contact / NC contact with wiring compartment

11 1 NO contact / 1 NC contact antivalent

(5)

without Cable

ST Male connector

T Conductor with strain relief

D DC 2-wire

(6)

without Standard connector version

2 Alternative connector
version

(7)

N n-type

