



TV12H236-20Z-M20

- Double-insulated
- Thermoplastic enclosure
- 30 mm x 58,5 mm x 30 mm
- 1 Cable entry M 20 x 1.5
- Mounting details to EN 50047
- Wide range of alternative actuators
- Lever angle adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	TV12H 236-20Z
	101136907
EAN (European Article Number)	4030661280790
eCI@ss number, Version 9.0	27-27-06-01

Approval - Standards

cULus
cCSAus
CCC
EAC

General data

Product name	T 236 roller lever 12 H IEC 60947-5-1 ISO 13849-1 BG-GS-ET-15
Housing construction form	Norm construction design
Actuator type to DIN EN 50047	A
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Lever material	Metal film
Roller material	Plastic
Gross weight	76 g

General data - Features

Number of auxiliary contacts	2
------------------------------	---

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	20,000,000 Operations
Actuating speed, minimum	4,122 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note Bounce duration	Bounce duration in accordance with actuating speed
Note (Switchover time)	Switchover time in accordance with actuating speed
Actuating torque, minimum	0.2 Nm
Positive break torque	0.2 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection
	0.75 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	108.5 mm
Length of sensor	46 mm
Width of sensor	30 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
----------------------	------

Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	Normally open contact (NO)
Switching principle	Creep circuit element
Switching frequency	5,000 /h

Notes

Note (General) Switch with 2 NO contacts are not for security tasks

Ordering code

Product type description:

(1)(2) 2(3)6-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

4S Plunger 4S

4R Roller plunger 4R

1R Offset roller lever 1R

K Offset roller lever K

3K Angle roller lever 3K

4K Angle roller lever 4K

K4 Angle roller lever K4

1H Roller lever 1H

7H Roller lever 7H

10H Rod lever 10H

12H Roller lever 12H

14H Roller lever 14H

AF Spring rod lever AF

RMS Brass roller

(3)

3 slim design

5 large design

(4)

02 2 NC contact

11 1 NO contacts/1 NC contact

20 2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)

without Cable entry M20

ID IDC method of termination

NPT Cable entry NPT 1/2"

ST M12 connector with A-coding

ST-2310 M12 connector with B-coding

(7)

1297 Enclosure with transverse slotted holes

(8)

2138 Roller lever 7H for position switches with safety function

(9)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: k236hf04


| 294,0 kB | .jpg | 101.953 x 300.214 mm - 289 x 851

Pixel - 72 dpi

| 229,2 kB | .png | 74.083 x 218.017 mm - 210 x 618

Pixel - 72 dpi

Dimension/Product/Basic




ID: 1-236g01

| 4,0 kB | .png | 74.083 x 73.378 mm - 210 x 208 Pixel - 72 dpi

| 115,0 kB | .jpg | 352.778 x 349.956 mm - 1000 x 992 Pixel - 72 dpi

Diagramm/Product/Travel




ID: kh235s04

| 1,6 kB | .png | 74.083 x 22.931 mm - 210 x 65 Pixel - 72 dpi

| 49,0 kB | .jpg | 352.778 x 109.714 mm - 1000 x 311 Pixel - 72 dpi

| 24,5 kB | .cdr |


Graphic/Product/Contact



ID: k--2sk01

| 51,9 kB | .jpg | 352.778 x 135.819 mm - 1000 x 385 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1h236g04

| 81,3 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697 Pixel - 72 dpi

| 79,1 kB | .cdr |

| 7,7 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 042021-01-31T03:51:04+01:000301Europe/BerlinSun, 31 Jan 2021 03:51:04

+010004amSunday.31am31Europe/BerlinCET5101Europe/BerlinJanuary2021Sun, 31 Jan 2021 03:51:04

+010001am31