XZCP1774L2

pre-wired connectors XZ - straight female - 7/8" - 5 pins - cable PUR 2m





Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

Complementary		
Electrical connection	Straight female connector 7/8"16 UN, 5 pins	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	2 m	
Cable outer diameter	5 mm	
Cable composition	5 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	250 V AC 300 V DC	
[In] rated current	4 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	
Net weight	0.24 kg	

Environment

Livioninent		
IP degree of protection	IP67	
Product certifications	CULus	
Ambient air temperature for operation	-4080 °C static -580 °C flexing	
Ambient air temperature for storage	-4080 °C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	94 g	
Package 1 Height	2 cm	
Package 1 width	16 cm	
Package 1 Length	16 cm	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End of Life Information


Contractual warranty

Warranty 18 months	

Product data sheet Dimensions Drawings

XZCP1774L2

Dimensions




L: Lenght of cable

Product data sheet Connections and Schema

XZCP1774L2

Connections and Schemes

Connector



BU: Blue BN: Brown BK: Black GY: Grey WH: White