

CE FC

Model Number

OHV2000-F221-B15

Handheld with Bluetooth for reading laser-engraved, etched, or printed 1-D and 2-D codes

Features

- All common 1-D or 2-D codes can be read
- Wireless Bluetooth connection
- Dual lens for large read range
- Reading of laser-engraved, etched, or printed codes
- Reads from reflective surfaces
- Programmable with JavaScript
- Batch mode for collecting data on the handheld
- Audible, tactile, and visual user feed-• back
- Replaceable battery with status indicator
- Degree of protection IP65 •

Pepperl+Fuchs Group

www.pepperl-fuchs.com


Function


ves

The OHV2000 handheld is a compact handheld reader for all common 1-D and 2-D codes applied directly to the surface of a product. For example, the code may have been etched, printed, or laser-engraved on the housing. Special technology to prevent glare allows the device to accurately read codes on highly reflective surfaces. With its patented dual lens and a resolution of 1.2 million pixels, it can read both small and large codes from a wide range of distances. A different-colored target projection makes it easier to see the relevant code. Feedback comes in the form of a visual or audible signal or a vibration.

Using the Vision Configurator software, rule sets can be created for formatting read results without the need for extensive programming work. This facilitates integration into ERP systems. The read data is transferred via the Bluetooth interface or by plugging the handheld reader into the charger. Thanks to its robust housing and IP65 protection, the handheld reader is also suitable for outdoor use.

Indicating / Operating means





1	Memory access	Green
2	Bluetooth	Green
3	Function indicator	Green
4	Trigger buttons	

Technical data				
General specifications				
Light type	Integrated LED lightning (red)			
Readable codes	1-D Codes: Codabar, Code 11, Code 32, Code 39, Code 93, Code 128, IATA 2 of 5, Interleaved 2 of 5, GS1 DataBar, Hong Kong 2 of 5, Matrix 2 of 5, MSI Plessey, NEC 2 of 5, Pharma- code, Plessey, Straight 2 of 5, Telepen, Trioptic, UPC/EAN/JAN Stacked 1-D Codes: GS1 Composite, MicroPDF, PDF417 2-D Codes: Aztec Code, Code 49, Codablock F, Data Matrix, Han Xin, MaxiCode, Micro QR, QR Code Postal Codes: Australian Post, Intelligent Mail, Japan Post, KIX Code, Korea Post, Planet, Postnet, UK Royal Mail, UPU ID-tags			
Read distance	40 310 mm depending on the code type			
Reading field	max. 190 mm x 290 mm			
Modul size	≥0.1 mm			
Ambient light limit	96890 Lux			
Target velocity	Stop			
Nominal ratings				
Camera				
Туре	CMOS			
Number of pixels	1280 x 960			
Image recording	real-time , manually triggered			
Indicators/operating means				
Function indicator	3 LEDs			
Key	3 programmable function keys			
Electrical specifications				
Supply	from Li-Ion battery			
Interface				
Physical	Bluetooth (Class II), USB 2.0			
Ambient conditions				
Ambient temperature	-20 55 °C (-4 131 °F)			
Storage temperature	-30 65 °C (-22 149 °F)			
Relative humidity	5 95 % non-condensing			
Shock and impact resistance	Withstands multible drops from 1.8 m / 6 ft onto a concrete surface			
Mechanical specifications				
Degree of protection	IP65			
Material				
Housing	plastic			
Mass	219 g (incl. battery)			
Dimensions	130 mm x 51 mm x 135 mm (l x w x h)			
General information				
Scope of delivery	Handheld reader + Lithium ion battery, 1300 mAh			
Compliance with standards and direction				

Standard conformity

Refer to "General Notes Relating to Pepperl+Fuchs Product Information" USA: +1 330 486 0001

fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 4411 fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091 fa-info@sg.pepperl-fuchs.com



1

Electromagnetic compatibility

Safety


Radio spectrum Standards ETSI EN 301489-1:V1.9.2 ETSI EN 301489-17:V2.2.1 EN 61000-6-1:2007 EN 61000-6-2:2005/AC:2005 EN 61000-6-3:2007/A1:2011/AC:2012 EN 61000-6-4:2007/A1:2011/AC:2012 EN 61000-6-4:2007/A1:2010/A12:2011/AC:2011 EN 60950-1:2006/A11:2009/A1:2010/A12:2011/AC:2011 EN 60950-1:2006/A11:2009/A1:2010/A12:2011/AC:2011 EN 60950-1:2008 ETSI EN 300328:V1.8.1 EN 50581:2012


Approvals and certificates

FCC approval

FCC ID: QQ6-BTR11

Dimensions





Accessories

Vision Configurator Operating software for camera-based sensors

OHV-CHARGER-B15 Charger for OHV200 with built-in Bluetooth modem

OHV-CHARGER Charger for OHV200

OHV-BAT Lithium ion battery, 1300 mAh

OHV-BAT-CHARGER Charger for OHV-BAT

Other suitable accessories can be found at www.pepperl-fuchs.com

2

