



EX-AZM 161SK-12/12K-024-3D

- Ex-Zone 22
- 6 Contacts
- Manual release
- Screw connection
- Clamping force 2000N
- Thermoplastic enclosure
- 130 mm x 114 mm x 30 mm
- cable entries 4 M 16 x 1.5
- Interlock with protection against incorrect locking.

Data

Ordering data

	EX-AZM 161SK-12/12K-024-3D
	101191458
EAN (European Article Number)	4030661350639
eCl@ss number, Version 9.0	27-27-26-03

Explosion protection

	EN 60079-0
	EN 60079-31
	EN 60947-5-1
	⊕ II 3D Ex tc IIIC T80°C Dc X
Manufacturer declaration	ATEX Zone 22

General data

	EX-AZM 161
	EN 60947-5-1
Active principle	electromechanical
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	470 g

General data - Features

Power to unlock	Yes
Manual release	Yes
Number of actuating directions	3
Number of auxiliary contacts	2
Number of safety contacts	4

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Actuating play in direction of actuation	5.5 mm
Impact energy, maximum	1 J
Latching force	5 N
positive break travel	10 mm
Positive break force, minimum	20 N
Actuating speed, maximum	1 m/s

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	5 mm
Cable cross-section of the cable glands, maximum	10 mm
	1 x 0.75 mm ²
	1 x 1.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	114 mm
Length of sensor	30 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-10 °C

Ambient temperature, maximum	+50 °C
------------------------------	--------

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Rated control voltage	24 VAC
Rated control voltage	24 VDC
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	2.5 A
Electrical power consumption, maximum	10 W
Switching element	NO contact, NC contact
Switching principle	Creep circuit element
Switching frequency	1,000 /h

Electrical data - Safety contacts

Current, Utilisation category AC-15	4 A
Current, Utilisation category DC13	2.5 A

Electrical data - Auxiliary contacts

Current, Utilisation category AC-15	4 A
Current, Utilisation category DC13	2.5 A

Scope of delivery

Included in delivery	Actuators must be ordered separately. Including Ex-certified screwed cable gland and screw plug
----------------------	--

Notes

Note (Manual release)	For maintenance, installation, etc. For manual release using M5 triangular key, available as accessory
-----------------------	---

Ordering code

Product type description:

EX-AZM 161 (1)-12/12-(2)K(3)-024-3D

(1)

SK Screw connection

CC Cage clamps

(2)

without Latching force 5 N

R Latching force 30 N

(3)

without Power to unlock

A Power to lock

Pictures


Photo/Product/Catalogue



ID: kexazf09

| 844,6 kB | .jpg | 352.778 x 300.919 mm - 1000 x 853
Pixel - 72 dpi
| 60,9 kB | .png | 74.083 x 63.147 mm - 210 x 179
Pixel - 72 dpi


Dimension/Product/Basic



ID: kazm1g09

| 137,3 kB | .cdr |
| 139,6 kB | .jpg | 352.778 x 298.097 mm - 1000 x 845
Pixel - 72 dpi
| 4,5 kB | .png | 74.083 x 62.442 mm - 210 x 177 Pixel
- 72 dpi


Diagramm/Product/Travel



ID: kazm1s07

| 102,8 kB | .jpg | 352.778 x 304.8 mm - 1000 x 864
Pixel - 72 dpi
| 2,9 kB | .png | 74.083 x 63.853 mm - 210 x 181 Pixel
- 72 dpi


Graphic/Product/Contact



ID: kazm1k29

| 111,9 kB | .jpg | 352.778 x 227.894 mm - 1000 x 646
Pixel - 72 dpi

Illustration/Product/Function



ID: kazm1a41

| 13,0 kB | .png | 74.083 x 35.983 mm - 210 x 102
Pixel - 72 dpi
| 105,3 kB | .jpg | 352.778 x 170.744 mm - 1000 x 484
Pixel - 72 dpi
| 48,4 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 202021-01-31T16:54:20+01:000401Europe/BerlinSun, 31 Jan 2021 16:54:20

+010020pmSunday.31pm31Europe/BerlinCET5401Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:54:20

+010001pm31