



BN 75-11Z-1391

- Long life
- Float switch
- 1 Reed contacts
- with Pre-wired cable
- Non-contact principle
- 80 mm x 99,5 mm x 55 mm
- Thermoplastic enclosure
- Available with M12 plug-in connector and pre-wired cable

Data

Ordering data

	BN 75-11Z-1391
	101055702
EAN (European Article Number)	4030661008998
eCl@ss number, Version 9.0	27-27-01-05

General data

	BN 75
Active principle	Magnetic drive
Housing construction form	Special construction
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Plastic
Gross weight	132 g

General data - Features

Number of openers	1
Number of shutters	1

Mechanical data

Actuating element	Magnet
Mechanical life, minimum	1,000,000,000 Operations

Hysteresis (Switch distance), 3 mm
maximum

Mechanical data - Connection technique

Terminal Connector Pre-wired cable

Mechanical data - Dimensions

Height of sensor 99.5 mm
Length of sensor 55 mm
Width of sensor 80 mm

Ambient conditions

IP67
Ambient temperature, -25 °C
minimum
Ambient temperature, +80 °C
maximum

Electrical data

Voltage type AC (alternating current)
Switching voltage, maximum 220 VAC
Switching current, maximum 1 A
Switching capacity, 60 W
maximum
Switching capacity, 60 VA
maximum
Switching element NO contact / NC contact
Bounce duration, minimum 0.2 ms
Bounce duration, maximum 0.5 ms

Electrical data - Digital Output

Versions Reed contacts

Notes

Note (General) The switching function is reversed accordingly, if the floater in a changeover contact element is turned upside-down. The operating points listed, apply for water.

Pictures

Photo/Product/Catalogue




ID: kbn75f01

| 560,2 kB | .jpg | 352.778 x 529.167 mm - 1000 x 1500 Pixel - 72 dpi

| 48,7 kB | .png | 74.083 x 111.125 mm - 210 x 315 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1bn75g01

| 24,8 kB | .cdr |

| 79,9 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693 Pixel - 72 dpi

| 4,0 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel - 72 dpi

Graphic/Product/Contact




ID: 1bn75k03

| 53,4 kB | .jpg | 352.778 x 244.475 mm - 1000 x 693 Pixel - 72 dpi

| 22,9 kB | .cdr |

Diagramm/Product/Curve



ID: kbn65d02

| 3,0 kB | .png | 74.083 x 87.842 mm - 210 x 249 Pixel - 72 dpi

| 106,3 kB | .jpg | 352.778 x 419.1 mm - 1000 x 1188 Pixel - 72 dpi

| 17,5 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 442021-01-31T16:27:44+01:000401Europe/BerlinSun, 31 Jan 2021 16:27:44

+010044pmSunday.31pm31Europe/BerlinCET2701Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:27:44

+010001pm31