

## Technical data sheet Reflector

Part no.: 50142993

BTU 934M-VKT+L-90

### Contents

- Technical data
- Dimensioned drawings



Figure can vary

## Technical data

### Basic data

|                |                                            |
|----------------|--------------------------------------------|
| Suitable for   | PRK retro-reflective photoelectric sensors |
| Pre-mounted on | TKA 30x46 reflector                        |

### Mechanical data

|                                             |                                     |
|---------------------------------------------|-------------------------------------|
| Design                                      | Rectangular                         |
| Reflection surface width                    | 46 mm x 30 mm                       |
| Reflector material                          | Plastic                             |
| Standard designation, metal mounting device | Aluminum                            |
|                                             | Steel, galvanized                   |
| Type of fastening                           | Clampable                           |
| Type of fastening, at system                | For 9-12 mm rods                    |
|                                             | Sheet metal mounting bracket 3-4 mm |
|                                             | Square rod 10 mm                    |
| Type of fastening, at device                | Pre-mounted reflector               |
| Type of mounting device                     | Clampable                           |
|                                             | Swiveling                           |
|                                             | Turning, 360°                       |
| Mounting device material                    | Metal                               |
| ITEM-compatible                             | No                                  |

### Environmental data

|                                |               |
|--------------------------------|---------------|
| Ambient temperature, operation | -40 ... 70 °C |
|--------------------------------|---------------|

### Classification

|                       |          |
|-----------------------|----------|
| Customs tariff number | 83024900 |
| eCl@ss 8.0            | 27279202 |
| eCl@ss 9.0            | 27273701 |
| ETIM 5.0              | EC003015 |
| ETIM 6.0              | EC003015 |

## Dimensioned drawings

All dimensions in millimeters

