


## Inductive power clamp sensor NBN2-F581-160S6-E10-V1

- Basic series
- Extremely bright triple luminous band indication
- M12 plug with safety screw assembly adjustable in 45° grid
- For use in direct- and alternating-field welding systems
- Completely halogen and silicon free



### Dimensions



### Technical Data

#### General specifications

|                            |       |                        |
|----------------------------|-------|------------------------|
| Switching function         |       | 2 x normally open (NO) |
| Output type                |       | NPN                    |
| Rated operating distance   | $s_n$ | 2 mm                   |
| Installation               |       | non-flush              |
| Output polarity            |       | DC                     |
| Assured operating distance | $s_a$ | 0 ... 1.62 mm          |
| Reduction factor $r_{AI}$  |       | 0.35                   |
| Reduction factor $r_{Cu}$  |       | 0.3                    |
| Reduction factor $r_{304}$ |       | 0.7                    |
| Output type                |       | 4-wire                 |

#### Nominal ratings

## Technical Data

|                             |       |                                                                                    |
|-----------------------------|-------|------------------------------------------------------------------------------------|
| Operating voltage           | $U_B$ | 10 ... 30 V DC                                                                     |
| Switching frequency         | $f$   | 0 ... 25 Hz                                                                        |
| Hysteresis                  | H     | 3 ... 20 % 5 typ.                                                                  |
| Reverse polarity protection |       | yes                                                                                |
| Short-circuit protection    |       | pulsing                                                                            |
| Voltage drop                | $U_d$ | $\leq 3$ V DC                                                                      |
| Operating current           | $I_L$ | 0 ... 100 mA                                                                       |
| Off-state current           | $I_r$ | $\leq 10$ $\mu$ A                                                                  |
| No-load supply current      | $I_o$ | $\leq 35$ mA                                                                       |
| Constant magnetic field     | B     | 100 mT                                                                             |
| Alternating magnetic field  | B     | 100 mT                                                                             |
| Operating voltage indicator |       | LED green                                                                          |
| Switching state indicator   |       | switching state "close" = LED red (S2)<br>switching state "open" = LED yellow (S1) |

### Functional safety related parameters

|                                |  |        |
|--------------------------------|--|--------|
| MTTF <sub>d</sub>              |  | 1445 a |
| Mission Time (T <sub>M</sub> ) |  | 20 a   |
| Diagnostic Coverage (DC)       |  | 0 %    |

### Compliance with standards and directives

|                     |  |                                                                                             |
|---------------------|--|---------------------------------------------------------------------------------------------|
| Standard conformity |  |                                                                                             |
| Standards           |  | EN 60947-5-2:2007<br>EN 60947-5-2/A1:2012<br>IEC 60947-5-2:2007<br>IEC 60947-5-2 AMD 1:2012 |

### Approvals and certificates

|              |  |                                                                    |
|--------------|--|--------------------------------------------------------------------|
| UL approval  |  | cULus Listed, General Purpose                                      |
| CCC approval |  | CCC approval / marking not required for products rated $\leq 36$ V |

### Ambient conditions


|                     |  |                                |
|---------------------|--|--------------------------------|
| Ambient temperature |  | -25 ... 70 °C (-13 ... 158 °F) |
| Storage temperature |  | -40 ... 85 °C (-40 ... 185 °F) |

### Mechanical specifications


|                               |  |                                                     |
|-------------------------------|--|-----------------------------------------------------|
| Connection type               |  | Connector plug M12 x 1 , 4-pin                      |
| Flexible lead, housing-sensor |  | 160 mm $\pm$ 5 mm , PUR (halogen-free)              |
| Housing material              |  | amplifier; PBT, PA6 + GD-ZN AL4<br>oscillators; PBT |
| Degree of protection          |  | IP67                                                |

## Connection

E10



## Connection Assignment



Wire colors in accordance with EN 60947-5-2

|   |    |         |
|---|----|---------|
| 1 | BN | (brown) |
| 2 | WH | (white) |
| 3 | BU | (blue)  |
| 4 | BK | (black) |

Release date: 2020-03-24 Date of issue: 2020-03-30 Filename: 801314\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**