

## BNS 260-11ZG-ST-L



- Long life
- Small body
- no mechanical wear
- 26 mm x 36 mm x 13 mm
- Insensitive to soiling
- Thermoplastic enclosure
- Connector M8 x 1, 4-pole
- Concealed mounting possible
- Insensitive to transverse misalignment

### Data

#### Ordering data

BNS 260-11ZG-ST-L

101184383

EAN (European Article Number) 4030661321837

eCl@ss number, Version 9.0 27-27-24-02

#### Approval - Standards

TÜV

cULus

EAC

#### General data

BNS 260

IEC 60947-5-3

BG-GS-ET-14

Installation conditions  
(mechanical)

quasi-flush

Enclosure material

Glass-fibre, reinforced thermoplastic

Gross weight

32 g

#### General data - Features

Coding

Yes

Integral System Diagnostics,  
status

Yes

|                           |   |
|---------------------------|---|
| Number of openers         | 1 |
| Number of shutters        | 1 |
| Number of safety contacts | 2 |

### Safety appraisal

|              |             |
|--------------|-------------|
|              | ISO 13849-1 |
| Mission Time | 20 Year(s)  |

### Safety appraisal - Safety outputs

|                                                                   |                       |
|-------------------------------------------------------------------|-----------------------|
| B10d- Value Normally-closed contact/Normally open contact (NC/NO) | 25,000,000 Operations |
|-------------------------------------------------------------------|-----------------------|

### Mechanical data

|                                               |                                                                                                                                                                                                                                                                                |
|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Actuating element                             | Magnet                                                                                                                                                                                                                                                                         |
| Door hinge                                    | Left                                                                                                                                                                                                                                                                           |
| Ensured switch distance "ON" S <sub>ao</sub>  | 5 mm                                                                                                                                                                                                                                                                           |
| Ensured switch distance "OFF" S <sub>ar</sub> | 15 mm                                                                                                                                                                                                                                                                          |
| Notice (Switch distance S <sub>n</sub> )      | Axial misalignment, a horizontal and vertical misalignment of the safety sensor and the actuator are tolerated. The possible misalignment depends on the distance of the active surfaces of the sensor and the actuator. The sensor remains active within the tolerance range. |
| Direction of motion                           | Head-on to the active surface                                                                                                                                                                                                                                                  |

### Mechanical data - Connection technique

|                    |              |
|--------------------|--------------|
| Terminal Connector | Connector M8 |
|--------------------|--------------|

### Mechanical data - Dimensions

|                  |       |
|------------------|-------|
| Height of sensor | 36 mm |
| Length of sensor | 13 mm |
| Width of sensor  | 26 mm |

### Ambient conditions

|                                            |                              |
|--------------------------------------------|------------------------------|
|                                            | IP67                         |
| Ambient temperature, minimum               | -25 °C                       |
| Ambient temperature, maximum               | +70 °C                       |
| Storage and transport temperature, minimum | -25 °C                       |
| Storage and transport temperature, maximum | +70 °C                       |
| Resistance to vibrations to EN 60068-2-6   | 10 ... 55 Hz, amplitude 1 mm |

30 g / 11 ms

## Electrical data

|                              |                     |
|------------------------------|---------------------|
| Voltage type                 | DC (direct current) |
| Switching voltage, maximum   | 24 VDC              |
| Switching current, maximum   | 0 A                 |
| Switching capacity, maximum  | 0.2 W               |
| Switching frequency, maximum | 5 Hz                |

## Status indication

|                                             |                                                  |
|---------------------------------------------|--------------------------------------------------|
| Note (Integral System Diagnostics, status ) | The LED is illuminated when the guard is closed. |
|---------------------------------------------|--------------------------------------------------|

## Scope of delivery

|                      |                                       |
|----------------------|---------------------------------------|
| Included in delivery | Actuators must be ordered separately. |
|----------------------|---------------------------------------|

## Accessory

BPS 260  
SRB-E-301ST  
SRB-E-201LC

## Notes

|                |                                                                  |
|----------------|------------------------------------------------------------------|
| Note (General) | The number in brackets indicate the PIN number of the connector. |
|----------------|------------------------------------------------------------------|

## Circuit example

|                       |                                                                            |
|-----------------------|----------------------------------------------------------------------------|
| Note (Wiring diagram) | The contacts S13-S14 and S21-S22 must be integrated in the safety circuit. |
|-----------------------|----------------------------------------------------------------------------|

## Ordering code

Product type description:

BNS 260-(1)(2)Z(3)-(4)-(5)

(1)

**11** 1 NO contacts/1 NC contact

**02** 2 NC contact

(2)

**without** with diagnostic output

**/01** 1 NC contact

(3)

**without** without LED switching conditions display  
**G** with LED switching conditions display

(4)  
**without** Pre-wired cable  
**ST** with connector

(5)  
**L** Door hinge on left-hand side  
**R** Door hinge on right-hand side


Pictures

Photo/Product/Catalogue



ID: kbns2f05  
  
| 42,7 kB | .png | 74.083 x 60.325 mm - 210 x 171  
Pixel - 72 dpi  
| 533,2 kB | .jpg | 352.778 x 287.161 mm - 1000 x 814  
Pixel - 72 dpi

Dimension/Product/Basic




ID: 1bns2g06  
  
| 65,1 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695  
Pixel - 72 dpi  
| 3,1 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel  
- 72 dpi  
| 25,6 kB | .cdr |

Graphic/Product/Contact



ID: kbns2k03  
  
| 18,7 kB | .cdr |  
| 59,6 kB | .jpg | 352.778 x 57.503 mm - 1000 x 163  
Pixel - 72 dpi

Diagramm/Product/Curve



ID: kbns2d03

| 200,1 kB | .jpg | 352.778 x 233.892 mm - 1000 x 663


Pixel - 72 dpi

| 18,5 kB | .png | 74.083 x 49.036 mm - 210 x 139

Pixel - 72 dpi

| 36,8 kB | .cdr |

## Diagramm/Product/Curve



ID: kbns2d02

| 200,9 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667


Pixel - 72 dpi

| 19,2 kB | .png | 74.083 x 49.389 mm - 210 x 140

Pixel - 72 dpi

| 36,3 kB | .cdr |

## Graphic/Clipart




ID: kbns2c02

| 19,6 kB | .cdr |

| 1,8 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel  
- 72 dpi

## Graphic/Product/PIN



ID: km8--k4b

| 17,0 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 162021-01-31T06:46:16+01:000601Europe/BerlinSun, 31 Jan 2021 06:46:16

+010016amSunday.31am31Europe/BerlinCET4601Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:46:16

+010001am31