

MZM100BST2-SD2PREM-A



- Patented
- Power to lock
- Automatic latching
- Actuator monitored
- Intelligent diagnosis
- Connector M12, 8-pole
- 40 mm x 179 mm x 40 mm
- Thermoplastic enclosure
- serial diagnostic output
- Self-monitoring series-wiring
- 3 LEDs to show operating conditions
- Electronic contact-free, coded system
- Max. length of the sensor chain 200 m
- Solenoid interlocks (for the protection of man) with innovating and unique operating principle
- Sensor technology permits an offset between actuator and interlock of ± 5 mm vertically and ± 3 mm horizontally

Data

Ordering data

MZM 100 B ST2-SD2PREM-A
101211153

EAN (European Article Number) 4030661389431

eCl@ss number, Version 9.0 27-27-26-03

Approval - Standards

TÜV
cULus
EAC

General data

MZM 100
IEC 61508

general information Universal coding

Coding level according to ISO 14119 Low

Active principle	inductive
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	620 g
Time to readiness, maximum	4,000 ms
Reaction time, maximum	150 ms
Duration of risk, maximum	150 ms

General data - Features

Power to lock	Yes
Actuator monitored	Yes
Serial diagnostics	Yes
Latching	Yes
Short circuit detection	Yes
Short-circuit recognition	Yes
Series-wiring	Yes
Safety functions	Yes
Integral System Diagnostics, status	Yes
Number of safety contacts	2
Number of Series-wiring of sensors	31

Safety appraisal

IEC 61508

Safety appraisal - Interlocking

Performance level, up to	e
Control category	4
PFH-value	$3.54 \times 10^{-9} /h$
Safety Integrity Level (SIL), applicable for	3
Mission Time	20 Year(s)

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Note (Mechanical lifetime)	Actuating speed < 0.5 m/s Operations for door weights ≤ 5 kg
Clamping force, typically	750 N
Clamping force, guaranteed	500 N
Latching force, minimum	45 N
Latching force, maximum	115 N

Mechanical data - Connection technique

Terminal Connector	Connector M12, 8-pole
--------------------	-----------------------

Mechanical data - Dimensions

Height of sensor	179 mm
Length of sensor	40 mm
Width of sensor	40 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529 IP 67 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+55 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Relative humidity, minimum	30 %
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing non-icing
Resistance to vibrations to EN 60068-2-6	10 ... 150 Hz, amplitude 0.35 mm 30 g / 11 ms III

Ambient conditions - Insulation value

Rated impulse withstand voltage	0.8 kV III 3
---------------------------------	------------------------

Electrical data

Operating voltage, minimum	20.4 VDC
Operating voltage, maximum	26.4 VDC
No-load current	600 mA
Operating current	50 mA
Required rated short-circuit current to EN 60947-5-1	100 A
Switching frequency, maximum	1 Hz

Note	Cable length and cable section alter the voltage drop depending on the output current
------	---

Electrical data - Solenoid control

-3 V ... 5 V (Low)
15 V ... 30 V (High)
C0
C1
C2
C3

Electrical data - Fail-safe digital inputs

-3 V ... 5 V (Low)
15 V ... 30 V (High)
C1
C1
C2
C3

Electrical data - Fail-safe digital outputs

Rated operating current (safety outputs)	250 mA
Voltage drop U_d , maximum	1 V
Current leakage	0.5 mA
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.3 A
	C1
	C1

Electrical data - Diagnostic output

Voltage drop U_d , maximum	2 V
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.1 A

Status indication

Note (LED switching conditions display)	Operating condition: LED green Error / functional defect: LED red Supply voltage UB: LED green
---	--

Pin assignment

PIN 1	A1 Supply voltage UB
PIN 2	X1 Safety input 1
PIN 3	A2 GND
PIN 4	Y1 Safety output 1
PIN 5	OUT serial diagnostic output
PIN 6	X2 Safety input 2
PIN 7	Y2 Safety output 2
PIN 8	IN serial diagnostic input

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

MZM 100-B1.1

Notes

Note (General)	As long as the actuating unit is applied to the solenoid interlock, the unlocked safety guard can be relocked. In this case, the safety outputs are re-enabled, so that the safety guard must not be opened.
----------------	--

Ordering code

Product type description:

MZM 100

(1)

ST Connector M23, (8+1 pole)

ST2 Connector M12, 8-pole

(2)

1P2PW 1 diagnostic output and 2 safety outputs, p-type, combined diagnostic signal: guard system closed and interlock locked

SD2P serial diagnostic output and 2 p-type safety outputs

(3)

without without latching force

RE electrically adjustable latching force 30 ... 100 N

(4)

M Permanent magnet approx. 30 N

(1)

ST Connector M23, (8+1 pole)

ST2 Connector M12, 8-pole

(2)

1P2PW2 1 diagnostic output and 2 safety outputs, all p-type and combined diagnostic signal: safety guard closed and solenoid interlock locked.

SD2P serial diagnostic output and 2 p-type safety outputs

(3)

M Permanent magnet approx. 30 N

NB, MBN, BN Actuator monitored

RE electrically adjustable latching force 30 ... 100 N

A Power to lock

Pictures

Photo/Product/Catalogue




ID: kmzm1f25

| 22,1 kB | .png | 74.083 x 100.189 mm - 210 x 284
Pixel - 72 dpi

| 273,6 kB | .jpg | 352.778 x 477.661 mm - 1000 x
1354 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1mzm1g14

| 160,8 kB | .jpg | 352.778 x 242.358 mm - 1000 x 687
Pixel - 72 dpi

| 5,2 kB | .png | 74.083 x 50.8 mm - 210 x 144 Pixel -
72 dpi


Dimension/Other



ID: 1mzm1g15

| 290,8 kB | .jpg | 352.425 x 362.656 mm - 999 x 1028
Pixel - 72 dpi

Graphic/Product/Wiring



ID: kmzm1l04

| 38,1 kB | .cdr |
| 83,1 kB | .jpg | 352.778 x 144.639 mm - 1000 x 410
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 302021-01-30T18:59:30+01:000601Europe/BerlinSat, 30 Jan 2021 18:59:30

+010030pmSaturday.30pm31Europe/BerlinCET5901Europe/BerlinJanuary2021Sat, 30 Jan 2021 18:59:30
+010001pm31