



T4VH 355-12ZUE

- Metal enclosure
- 66,7 mm x 76 mm x 38 mm
- Mounting details to EN 50041
- Switching points to EN 50041
- 3 cable entries lateral M 20 x 1.5
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

T4VH 355-12ZUE

101148292

eCl@ss number, Version 9.0

27-27-26-01

General data

Product name	T 355 roller lever H
Housing construction form	Norm construction design
	A
Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Lever material	Metal film
Roller material	Plastic
Gross weight	315 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	2

Safety appraisal

BG-GS-ET-15
ISO 13849-1
EN 60947-5-1

Mission Time

20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)

20,000,000 Operations

Mechanical data

Actuating element

Roller lever

Mechanical life, minimum

30,000,000 Operations

Actuating speed, maximum

2.5 m/s

Note (Actuating speed)

Actuating speed with actuating angle 30° to switch axis

Note (Switchover time)

Switchover time in accordance with actuating speed

Actuating torque, minimum

0.3 Nm

Mechanical data - Connection technique

Terminal Connector

Screw connection

0.75 mm²

2.5 mm²

Note (Cable section)

All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor

129.5 mm

Length of sensor

60.6 mm

Width of sensor

66.7 mm

Ambient conditions

IP67

Ambient temperature, minimum

-30 °C

Ambient temperature, maximum

+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage

4 kV

Electrical data

Thermal test current

10 A

Required rated short-circuit current to EN 60947-5-1

1,000 A

Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	NO contact, NC contact
Switching principle	Slow action with overlapping contacts
Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Ordering code

Product type description:

(1)(2) 3(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

1K Offset roller lever 1K

3K Angle roller lever 3K

RMS Brass roller

(3)

3 slim design

5 large design

(4)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

01/01 1 NC contact left / 1 NC contact right

12 1 NO contact/2 NC contacts

03 3 NC contact

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)

G24 with LED

(7)

without Cable entry M20

NPT Cable entry NPT 1/2"

ST M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

ST-2310 M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

(8)

2138 Roller lever 7H for position switches with safety function

(9)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: k355hf01


| 469,8 kB | .jpg | 208.844 x 338.667 mm - 592 x 960

Pixel - 72 dpi

| 80,7 kB | .png | 74.083 x 119.944 mm - 210 x 340

Pixel - 72 dpi

Dimension/Product/Basic



ID: 1x355g01

| 10,6 kB | .png | 74.083 x 51.506 mm - 210 x 146

Pixel - 72 dpi


| 132,5 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695

Pixel - 72 dpi

| 32,9 kB | .cdr |


Diagramm/Product/Travel

ID: kh335s19



| 94,1 kB | .jpg | 352.778 x 141.817 mm - 1000 x 402
Pixel - 72 dpi
| 3,0 kB | .png | 74.083 x 29.633 mm - 210 x 84 Pixel -
72 dpi
| 34,6 kB | .cdr |


Graphic/Product/Contact



ID: k2o1sk02

| 18,4 kB | .cdr |
| 82,3 kB | .jpg | 352.778 x 193.322 mm - 1000 x 548
Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1h336g01

| 84,5 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701
Pixel - 72 dpi
| 65,6 kB | .cdr |
| 4,1 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 202021-01-31T05:11:20+01:000501Europe/BerlinSun, 31 Jan 2021 05:11:20

+010020amSunday.31am31Europe/BerlinCET1101Europe/BerlinJanuary2021Sun, 31 Jan 2021 05:11:20

+010001am31