

CSS 8-180-2P-E-LST



- Connector M12, 4-pole
- Thermoplastic enclosure

- Misaligned actuation possible
- Electronic contact-free, coded system
- Max. length of the sensor chain 200 m
- 2 short-circuit proof PNP safety outputs
- Self-monitoring series-wiring of 16 sensors
- High repeat accuracy of the switching points
- Early warning when operating near the limit of the sensor's hysteresis range

Data

Ordering data

	CSS 8-180-2P-E-LST
	101167897
EAN (European Article Number)	4030661219516
eCl@ss number, Version 9.0	27-27-24-03

Approval - Standards

IFA
cULus
EAC

General data

	CSS 180
	IEC 61508
	IEC 60947-5-3
Active principle	inductive
Housing construction form	Cylinder, thread

Installation conditions (mechanical)	not flush
Sensor topology	Individual sensor or end sensor in a series
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Glass-fibre, reinforced thermoplastic
Material of the nuts	Glass-fibre, reinforced thermoplastic
Gross weight	140 g
Reaction time, maximum	30 ms
Duration of risk, maximum	30 ms

General data - Features

Short circuit detection	Yes
Short-circuit recognition	Yes
Safety functions	Yes
Integral System Diagnostics, status	Yes
Number of fail-safe digital outputs	2
Number of Series-wiring of sensors	16

Safety appraisal

	ISO 13849-1 IEC 60947-5-3 IEC 61508
Performance level, up to	e
Control category to EN13849	4
PFH-value	$2.50 \times 10^{-9} /h$
Safety Integrity Level (SIL), applicable for	3
Mission Time	20 Year(s)

Mechanical data

Switch distance	8 mm
Ensured switch distance "ON" S_{ao}	7 mm
Ensured switch distance "OFF" S_{ar}	10 mm
Hysteresis (Switch distance), maximum	0.7 mm
Repeat accuracy R R	0.2 mm

Tightening torque of
nuts, maximum 3 Nm

Mechanical data - Connection technique

Terminal Connector Cable with connector
Length of cable 2 m
Terminal connector,
Output M12 connector, 4 pole

Mechanical data - Dimensions

width across flats 24 BK
Length of sensor 92 mm

Ambient conditions

Protection class IP 65 to IEC/EN 60529
IP 67 to IEC/EN 60529
Ambient temperature,
minimum -25 °C
Ambient temperature,
maximum +60 °C
Storage and transport
temperature, minimum -25 °C
Storage and transport
temperature, maximum +85 °C
Resistance to
vibrations to EN 60068- 10 ... 55 Hz, amplitude 1 mm
2-6
30 g / 11 ms
II

Ambient conditions - Insulation value

Rated impulse
withstand voltage 0.8 kV
III
3

Electrical data

Voltage type DC (direct current)
Operating voltage,
minimum 20.4 VDC
Operating voltage,
maximum 26.4 VDC
No-load current 50 mA

	24 VDC
Operating current	1,000 mA
Switching frequency, approx.	3 Hz

Electrical data - Fail-safe digital outputs

Rated operating current (safety outputs)	500 mA
Output current, (fail- safe output), maximum	0.5 A
Versions	p-type
Voltage drop U_d , maximum	0.5 V
Current leakage	0.5 mA
Voltage, Utilisation category DC12	24 VDC
Current, Utilisation category DC12	0.5 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.5 A

Status indication

Note (LED switching conditions display)	Multi-coloured LED: Green, Red, Yellow
--	--

Pin assignment

PIN 1	1A1 Ue: (1)
PIN 2	Y2 Safety output 2
PIN 3	A2 GND
PIN 4	Y1 Safety output 1

Scope of delivery

Included in delivery	Actuators must be ordered separately.
Delivery scope of Mounting material	2x nuts M18 x 1

Accessory

CST 180-1
CST 180-2
PROTECT PSC1
SRB-E-301ST
SRB-E-201LC

Notes

Note (General) Evaluation requirements: dual-channel safety input, suitable for p-type sensors with NO function. The safety-monitoring module must tolerate internal functional tests of the sensors with cyclic switch-off of the sensor outputs for max. 0.25 ms. Short-circuit recognition by the evaluation is not necessary.

Ordering code

Product type description:

CSS 8-180-(1)-(2)-(3)

(1)

2P 2 short-circuit proof PNP safety outputs

2P+D 2 short-circuit proof PNP safety outputs and diagnostic output

(2)

E Individual sensor or end sensor in a series

Y Series-wiring

M Multifunction connection

(3)

L Cable

LST Cable with connector

ST Connector plug

Pictures

Photo/Product/Catalogue




ID: kcs18f01

| 15,4 kB | .png | 74.083 x 34.572 mm - 210 x 98 Pixel
- 72 dpi

| 188,8 kB | .jpg | 352.778 x 164.747 mm - 1000 x 467
Pixel - 72 dpi

Dimension/Product/Basic

ID: 1css1g01




| 24,2 kB | .cdr |

| 54,5 kB | .jpg | 352.778 x 140.758 mm - 1000 x 399
Pixel - 72 dpi

| 4,9 kB | .png | 74.083 x 29.633 mm - 210 x 84 Pixel -
72 dpi

Diagramm/Product/Curve



ID: kcsc1d03

| 3,0 kB | .png | 74.083 x 35.278 mm - 210 x 100 Pixel
- 72 dpi

| 83,4 kB | .jpg | 352.778 x 168.275 mm - 1000 x 477
Pixel - 72 dpi

| 22,0 kB | .cdr |

Graphic/Product/Wiring



ID: kcs18f21

| 127,3 kB | .jpg | 352.778 x 178.858 mm - 1000 x 507
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 522021-01-31T06:10:52+01:000601Europe/BerlinSun, 31 Jan 2021 06:10:52

+010052amSunday.31am31Europe/BerlinCET1001Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:10:52

+010001am31