



UV7H 434Y-1S/3OE

- 4 Contacts
- Metal enclosure
- 3 cable entries M 20 x 1.5
- Lever can be transposed by 180°
- 62 mm x 127 mm x 50 mm (basic component)
- Continuous adjustment of lever position 360°
- Switching points and contact function adjustable
- Actuator head can be repositioned in steps 4 x 90°

Data

Ordering data

	UV7H 434Y-1S/3OE
	101060639
eCl@ss number, Version 9.0	27-27-06-01

General data

Product name	U 434 roller lever 7H EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic

General data - Features

Number of openers	3
Number of shutters	1

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 1.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 1.5 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	262 mm
Length of sensor	50 mm
Width of sensor	62 mm
Width of Castor	9 mm
Diameter of Castor	36 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Electrical data

Thermal test current	16 A
Switching element	NC contact NO contact
Switching principle	Creep circuit element

Notes

Note (General)	Type of contact and switching points can be factory set to order.
----------------	---

Ordering code

Product type description:

U(1) 434Y-(2)-(3)

(1)

S Plunger S
K Offset roller lever K
8H Roller lever 8H
H Roller lever H
3H Roller lever 3H
7H Roller lever 7H
4H Spring rod lever on shaft 4H
9H Rod lever 9H
10H Rod lever 10H
2H Leaf spring lever 2H
6H Leaf spring lever 6H

(2)

without 2 NO contacts/2 NC contact
4OE 4 NC contact
4S 4 NO contacts
1S/3OE 1 NO contacts/3 NC contact
3S/1OE 3 NO contacts/1 NC contact

(3)

1272 Version for low temperatures to -30 °C

Pictures

Photo/Product/Catalogue



ID: ku43sf04

| 65,9 kB | .png | 74.083 x 120.297 mm - 210 x 341

Pixel - 72 dpi

| 978,8 kB | .jpg | 352.425 x 573.617 mm - 999 x 1626

Pixel - 72 dpi

Photo/Product/Catalogue



ID: ku43hf34


| 505,9 kB | .jpg | 135.114 x 433.564 mm - 383 x 1229

Pixel - 72 dpi

| 176,3 kB | .png | 74.083 x 237.419 mm - 210 x 673

Pixel - 72 dpi

Dimension/Product/Basic



ID: 1u43-g04

| 4,2 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel

- 72 dpi

| 91,2 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703

Pixel - 72 dpi

| 27,6 kB | .cdr |

Diagramm/Product/Travel



ID: ku43-s03


| 93,9 kB | .jpg | 352.778 x 182.386 mm - 1000 x 517

Pixel - 72 dpi

| 1,2 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel

- 72 dpi

Graphic/Product/Contact




ID: k3o1sk02

| 19,1 kB | .cdr |

| 82,7 kB | .jpg | 352.778 x 379.236 mm - 1000 x 1075

Pixel - 72 dpi

Illustration/Product/Function



ID: ku432a01

| 19,8 kB | .png | 74.083 x 49.742 mm - 210 x 141

Pixel - 72 dpi

| 203,1 kB | .cdr |

| 157,4 kB | .jpg | 352.778 x 236.361 mm - 1000 x 670

Pixel - 72 dpi

Illustration/Product/Function



ID: 235hz02


| 16,8 kB | .cdr |

| 212,6 kB | .jpg | 352.778 x 870.656 mm - 1000 x 2468 Pixel - 72 dpi

| 3,8 kB | .png | 74.083 x 182.739 mm - 210 x 518

Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t15vb05

| 10,5 kB | .png | 74.083 x 51.858 mm - 210 x 147

Pixel - 72 dpi

| 108,3 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 302021-01-31T15:42:30+01:000301Europe/BerlinSun, 31 Jan 2021 15:42:30

+010030pmSunday.31pm31Europe/BerlinCET4201Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:42:30

+010001pm31