

AZM190-02/01RK-MPVD-230VAC-2860



- Long life
- Wiring compartment
- Cut clamp termination
- 89 mm x 178 mm x 41 mm
- Thermoplastic enclosure
- 2 cable entries M 20 x 1.5
- Actuating head can be repositioned by 4 x 90°
- Sealing mechanism to prevent the ingress of dirt
- Interlock with protection against incorrect locking.
- Slim design, particularly suitable for fitting on hinged doors, aluminium profiles and fencing

Data

Ordering data

	AZM190-02/01RK-MPVD-230VAC-2860
	133007270
EAN (European Article Number)	8905236101205
eCl@ss number, Version 9.0	27-27-26-03
Replacement article number	103007270

Approval - Standards

cULus
CCC
EAC

General data

	EN 60947-5-1
	BG-GS-ET-19
Coding level according to ISO 14119	Low
Active principle	electromechanical
Enclosure material	Glass-fibre, reinforced thermoplastic
Material of the contacts, electrical	Silver
Gross weight	617 g

General data - Features

Power to unlock	Yes
Number of actuating directions	4
Number of safety contacts	3

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
B10d Normally open contact (NO)	1,000,000 Operations

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Clamping force	1,950 N
Latching force	20 N
Positive break force, minimum	20 N
Actuating speed, maximum	0.3 m/s

Mechanical data - Connection technique

Terminal Connector	Screw terminals 1 x 0.5 mm ² 1 x 1.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	178 mm
Length of sensor	41 mm
Width of sensor	52 mm

Ambient conditions

Protection class	IP 67 to IEC/EN 60529
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+50 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	4 A
Rated control voltage	230 VAC
Required rated short-circuit current to EN 60947-5-1	1,000 A
Electrical power consumption, maximum	8.5 W
Switching element	Opener (NC)
Switching principle	Creep circuit element
Switching frequency	1.2 /h

Electrical data - Safety contacts

Voltage, Utilisation category AC15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	4 A

Electrical data - Auxiliary contacts

Voltage, Utilisation category AC15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	4 A

Other data

Note (applications)	sliding safety guard removable guard hinged safety guard
---------------------	--

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Notes

Note (Manual release)	front For maintenance, installation, etc.
-----------------------	--

Ordering code

Product type description:

AZM190-(1)RK(2)(3)-(4)-(5)

(1)

02/01 Magnet: 2 NC contacts; actuator: 1 NC contact
02/02 Magnet: 2 NC contacts; actuator: 2 NC contacts
02/10 Magnet: 2 NC contacts; actuator: 1 NO contact
02/11 Magnet: 2 NC contacts; actuator: 1 NC contact/1 NO contact
11/01 Magnet: 1 NC contact/1 NO contact; actuator: 1 NC contact
11/02 Magnet: 1 NC contact/1 NO contact; actuator: 2 NC contacts
11/10 Magnet: 1 NC contact/1 NO contact; actuator: 1 NO contact
11/11 Magnet: 1 NC contact/1 NO contact; actuator: 1 NC contact/1 NO contact

(2)

without Power to unlock

A Power to lock

(3)

without With manual release on the cover side

E0 Without manual release

E1 With manual release from side (right)

N Emergency release

T Emergency exit

(4)

without without LED switching conditions display

G With LED switching conditions display (for 24 V AC/DC only; cannot be combined with -E1 and -T)

(5)

24VAC Us: 24 VAC

24 VDC Us: 24 VDC

48VAC Us: 48 VAC

110VAC Us: 110 VAC

230VAC Us: 230 VAC

Pictures

Photo/Product/Catalogue



ID: kapl-f01


| 736,6 kB | .jpg | 229.658 x 625.122 mm - 651 x 1772

Pixel - 72 dpi

| 108,5 kB | .png | 74.083 x 201.436 mm - 210 x 571

Pixel - 72 dpi

Dimension/Product/Basic



ID: kazm1g26

| 203,5 kB | .jpg | 352.778 x 396.522 mm - 1000 x 1124 Pixel - 72 dpi

| 6,9 kB | .png | 74.083 x 83.256 mm - 210 x 236 Pixel
- 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 162021-01-30T20:32:16+01:000801Europe/BerlinSat, 30 Jan 2021 20:32:16

+010016pmSaturday.30pm31Europe/BerlinCET3201Europe/BerlinJanuary2021Sat, 30 Jan 2021 20:32:16
+010001pm31