

- 



Technical drawing of the LED strip light assembly showing dimensions and components. The drawing includes the following specifications:

- Thread: M12 x 1
- Mounting hole diameter: 4
- Mounting hole offset: 8
- LEDs: 17
- Dimensions (mm): 53.5, 58.5, 65, 72, 75, 82
- Length: 1/2" - 20

General specifications

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Technical Data

Hysteresis	H	3 ... 15 typ. 5 %
Reverse polarity protection		reverse polarity tolerant
Short-circuit protection		yes
Voltage drop	U _d	≤ 8 V
Operating current	I _L	8 ... 200 mA AC/DC
Off-state current	I _r	≤ 0.8 mA
Operating voltage indicator		LED, green
Switching state indicator		LED, yellow

Compliance with standards and directives

Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007

Approvals and certificates

UL approval		cULus Listed, General Purpose
CSA approval		cCSAus Listed, General Purpose
CCC approval		Certified by China Compulsory Certification (CCC)

Ambient conditions

Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
---------------------	--	--------------------------------


Mechanical specifications

Connection type		Connector 1/2"-20 UN , 3-pin
Housing material		brass, nickel-plated
Sensing face		PBT
Degree of protection		IP67


General information

Scope of delivery		2 self locking nuts in scope of delivery
-------------------	--	--

Connection



Connection Assignment



Wire colors

1	GN (green)
2	RD/BK (red/black)
3	RD/WH (red/white)

Accessories

	EXG-12	Quick mounting bracket with dead stop
	V12-G-YE2M-PVC	Connecting cable, 1/2" - 20 UNF, 3-pin, PVC cable

Release date: 2020-03-23 Date of issue: 2020-03-30 Filename: 197869_eng.pdf