



EX-T1K 335-11Z-3G/D

- Metal enclosure
- Ex-Zone 2 and 22
- 40,5 mm x 76 mm x 38 mm
- 1 Cable entry M 20 x 1.5
- Mounting details to EN 50041
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	EX-T1K 335-11Z-3G/D
	101210701
EAN (European Article Number)	4030661387468
eCl@ss number, Version 9.0	27-27-26-01

Explosion protection

BG-GS-ET-15
 EN 60079-0
 EN 60079-15
 EN 60079-31
 EN 60947-5-1
 22
 2
 3D
 3G
 Ⓢ II 3G Ex nC IIC T5 Gc X
 Ⓢ II 3D Ex tc IIIC T90°C Dc X

Manufacturer declaration	ATEX Zone 2 and 22
--------------------------	--------------------

General data

Product name	EX-T 335 offset roller lever 1K
Housing construction form	Norm construction design
Enclosure material	Aluminium
Enclosure coating material	painted

Material of the contacts, electrical	Silver
Gross weight	237.5 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Offset roller lever
Mechanical life, minimum	30,000,000 Operations
Impact energy, maximum	4 J
Actuating force, minimum	17 N
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note (Switchover time)	Switchover time in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	7 mm
Cable cross-section of the cable glands, maximum	12 mm
	0.75 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	118.5 mm
Length of sensor	38 mm
Width of sensor	40.5 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Slow action
Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Ordering code

Product type description:

EX-(1)(2) 335-(3)Z(4)-(5)-(6)-(7)-3G/D

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

7H-2138 Roller lever 7H for position switches with safety function

1K Offset roller lever 1K

3K Angle roller lever 3K

(3)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

03 3 NC contact

UE Slow action with overlapping contacts

1297 Enclosure with transverse slotted holes

2138 Roller lever 7H for position switches with safety function

1637 Gold-plated contacts

Dimension/Product/Basic

ID: 1xzm1g07

| 2,5 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 46,3 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

Diagramm/Product/Travel

ID: kk335s14

| 42,7 kB | .jpg | 352.778 x 111.831 mm - 1000 x 317
Pixel - 72 dpi

| 25,5 kB | .cdr |

| 1,8 kB | .png | 74.083 x 23.636 mm - 210 x 67 Pixel - 72 dpi

Graphic/Product/Contact

ID: k1o1sk01

| 52,2 kB | .jpg | 352.778 x 143.581 mm - 1000 x 407
Pixel - 72 dpi

Dimension/Product/Actuator

ID: 1k336g01

| 71,4 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi

| 7,0 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

| 57,2 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 142021-01-31T17:36:14+01:00501Europe/BerlinSun, 31 Jan 2021 17:36:14

```
+010014pmSunday.31pm31Europe/BerlinCET3601Europe/BerlinJanuary2021Sun, 31 Jan 2021 17:36:14
+010001pm31
```