Product data sheet Characteristics

XZCPY4275L2

pre-wired connectors XZ - straight female - 7/8" - 4 pins - cable PVC 2m





Main Accessory / separate part category Accessory / separate Pre-wired connectors part type Series name General purpose



Complementary

Electrical connection	Straight female connector 7/8", 4 pins
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	2 m
Cable outer diameter	10.8 mm
Cable composition	4 x 1.5 mm²
Wire insulation material	PVC
[Ue] rated operational voltage	600 V AC 600 V DC
[In] rated current	10 A
Contact resistance	5000 μOhm
Minimum insulating resistance	1 GΩ
Net weight	0.34 kg

Environment

IP degree of protection	IP67
Product certifications	CULus
Ambient air temperature for operation	-2580 °C static
Ambient air temperature for storage	-2580 °C

Packing Units

Package 1 Weight	0.330 kg	
Package 1 Height	0.350 dm	
Package 1 width	2.200 dm	
Package 1 Length	2.400 dm	

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	⊈ Yes


Contractual warranty

	40
Warranty	18 months
vvarranty	10 Horitis

Product data sheet Dimensions Drawings

XZCPY4275L2

Dimensions




L: Lenght of cable

Product data sheet Connections and Schema

XZCPY4275L2

Connections and Schemes

Connectors



RD : Red WH : White BK : Black GN : Green