



RLDEWS24

- white LED
- 24 VAC/DC
- Screw connection
- Mounting flange position 3

Data

Ordering data

	RLDEWS24
	101195136
EAN (European Article Number)	4030661487366
eCl@ss number, Version 9.0	27-37-13-02

Approval - Standards

cURus
EAC

General data

Product name	Light terminal block RLDE EN 60947-5-1 IEC/EN 60947-1
Installation conditions (mechanical)	arbitrarily
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	23 g

General data - Features

Integral System Diagnostics, general	Yes
--------------------------------------	-----

Mechanical data

Installation instructions	pluggable 3
---------------------------	----------------

Mechanical data - Connection technique

Terminal Connector	Screw connection
Terminal designations	EN 50013
Cable section, minimum	0.5 mm ² , rigid 0.5 mm ² , flexible
Cable section, maximum	2.5 mm ² , rigid 1.5 mm ² , flexible
Tightening torque of Clips	1 Nm

Mechanical data - Dimensions

Width	10 mm
Length	46 mm
Depth	45 mm

Ambient conditions

	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+75 °C

Status indication

Colour of the LED	White
Note (LED switching conditions display)	Supply voltage UB: 24 VAC/DC

Pictures

Photo/Product/Catalogue



ID: krdlef02

| 41,6 kB | .png | 73.731 x 75.494 mm - 209 x 214
Pixel - 72 dpi
| 452,6 kB | .jpg | 352.778 x 360.539 mm - 1000 x
1022 Pixel - 72 dpi

ID: krdlek01



| 33,5 kB | .jpg | 352.778 x 79.022 mm - 1000 x 224

Pixel - 72 dpi

| 16,9 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 272021-01-31T14:39:27+01:000201Europe/BerlinSun, 31 Jan 2021 14:39:27

+010027pmSunday.31pm31Europe/BerlinCET3901Europe/BerlinJanuary2021Sun, 31 Jan 2021 14:39:27

+010001pm31