



PS216-T11-Q200

- Small body
- vertical mounting
- Twisting of towing eye not possible
- Progress function (ballpoint pen principle)
- thermoplastic enclosure with foldable latching cover

Data

Ordering data

PS216-T11-Q200

103032511

EAN (European Article Number)

4030661546209

Approval - Standards

cULus

EAC

General data

Housing construction form	Norm construction design
Material of the contacts, electrical	Silver
Length of the wire, maximum	50 m

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Mechanical data

Mechanical life, minimum	100,000 Operations
Positive break force, minimum	45 N
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	1 m/s

Mechanical data - Connection technique

Terminal Connector	Screw connection
	0.34 mm ²
	1.5 mm ²

Mechanical data - Dimensions

Height of sensor	116 mm
Length of sensor	32.5 mm
Width of sensor	31 mm

Ambient conditions

	IP66
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C
	II

Ambient conditions - Insulation value

III
3

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	400 A
Utilisation category AC-15	3 A
Utilisation category DC-13	3 A
Switching element	1 NO contact, 1 NC contacts
Switching principle	Slow action

Ordering code

Product type description:

PS216-(1)-(2)-(3)

(1)

T11 Slow action 1 NO contact / 1 NC contact

T20 Slow action 2 NO contact

T02 Slow action 2 NC contacts

T03 Slow action 3 NC contacts

T12 Slow action 1 NO contact / 2 NC contact

T21 Slow action 2 NO contact / 1 NC contact

without Cable entry M20

ST Connector plug M12 - plastic - bottom

(3)

Pictures

Photo/Product/Catalogue




ID: kps2qf03

| 1,4 MB | .jpg | 352.778 x 1292.225 mm - 1000 x 3663 Pixel - 72 dpi

| 144,5 kB | .png | 74.083 x 271.286 mm - 210 x 769
Pixel - 72 dpi


Dimension/Product/Basic



ID: kps216g03

| 140,4 kB | .jpg | 352.425 x 410.281 mm - 999 x 1163
Pixel - 72 dpi


Graphic/Product/Contact



ID: kps216k01

| 54,7 kB | .jpg | 352.778 x 106.186 mm - 1000 x 301
Pixel - 72 dpi

Graphic/Product/Mounting



ID: kps216m01

| 157,7 kB | .jpg | 352.425 x 505.531 mm - 999 x 1433
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 522021-01-31T02:38:52+01:000201Europe/BerlinSun, 31 Jan 2021 02:38:52

+010052amSunday.31am31Europe/BerlinCET3801Europe/BerlinJanuary2021Sun, 31 Jan 2021 02:38:52

+010001am31