



T4S 256-20Z

- Double-insulated
- Thermoplastic enclosure
- 58 mm x 50,5 mm x 31 mm
- 2 cable entries M 20 x 1.5
- Mounting details to EN 50047
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

T4S 256-20Z

101112748

eCl@ss number, Version 9.0

27-27-06-01

General data

Product name	T 256 plunger with central mounting 4S IEC 60947-5-1 ISO 13849-1 BG-GS-ET-15
Housing construction form	Norm construction design
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	105 g

General data - Features

Number of auxiliary contacts	2
------------------------------	---

Safety appraisal

Mission Time	ISO 13849-1 20 Year(s)
--------------	---------------------------

Mechanical data

Actuating element	Plunger
Mechanical life, minimum	20,000,000 Operations
Actuating force, minimum	9 N
Positive break force, minimum	19 N
Actuating speed, minimum	60 mm/min
Actuating speed, maximum	1 m/s
Note Bounce duration	Bounce duration in accordance with actuating speed
Note (Switchover time)	Switchover time in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection 0.75 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	90.5 mm
Length of sensor	31 mm
Width of sensor	58 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	Normally open contact (NO)
Switching principle	Creep circuit element
Switching frequency	5,000 /h

Notes

Note (General)

Switch with 2 NO contacts are not for security tasks

Ordering code

Product type description:

(1)(2) 2(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

4S Plunger 4S

4R Roller plunger 4R

1R Offset roller lever 1R

K Offset roller lever K

3K Angle roller lever 3K

4K Angle roller lever 4K

K4 Angle roller lever K4

1H Roller lever 1H

7H Roller lever 7H

10H Rod lever 10H

12H Roller lever 12H

14H Roller lever 14H

AF Spring rod lever AF

RMS Brass roller

(3)

3 slim design

5 large design

(4)

02 2 NC contact

11 1 NO contacts/1 NC contact

20 2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)	
without	Cable entry M20
ID	IDC method of termination
NPT	Cable entry NPT 1/2"
ST	M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)
ST-2310	M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

(7)
2574 Enclosure with L-shaped mounting holes (horizontally or vertically adjustable)

(8)
2138 Roller lever 7H for position switches with safety function

(9)
1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: k256sf02

| 92,4 kB | .png | 73.731 x 110.419 mm - 209 x 313
Pixel - 72 dpi
| 383,4 kB | .jpg | 182.033 x 271.992 mm - 516 x 771
Pixel - 72 dpi


Diagramm/Product/Travel



ID: kr235s10

| 1,6 kB | .png | 74.083 x 22.578 mm - 210 x 64 Pixel -
72 dpi
| 23,4 kB | .cdr |
| 36,8 kB | .jpg | 352.778 x 106.892 mm - 1000 x 303
Pixel - 72 dpi


Graphic/Product/Contact



ID: k--2sk01

| 51,9 kB | .jpg | 352.778 x 135.819 mm - 1000 x 385
Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1s236g02

| 7,5 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi
| 133,3 kB | .cdr |
| 82,3 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 112021-01-31T04:13:11+01:000401Europe/BerlinSun, 31 Jan 2021 04:13:11

+010011amSunday.31am31Europe/BerlinCET1301Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:13:11

+010001am31