



T4VH335-20ZH

- Metal enclosure
- Design to EN 50041
- 40,5 mm x 76 mm x 38 mm
- 1 Cable entry M 20 x 1.5
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	T4VH 335-20ZH
	101082544
EAN (European Article Number)	4030661065250
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

cULus
CCC
EAC

General data

Product name	T 335 roller lever H
Housing construction form	Norm construction design
	A
Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Lever material	Metal film
Roller material	Plastic
Gross weight	275 g

General data - Features

Number of auxiliary contacts	2
------------------------------	---

Safety appraisal

BG-GS-ET-15
ISO 13849-1
EN 60947-5-1

Mission Time

20 Year(s)

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	30,000,000 Operations
Actuating speed, maximum	2.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note (Switchover time)	Switchover time in accordance with actuating speed
Actuating torque, minimum	0.3 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection 0.75 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	134 mm
Length of sensor	60.6 mm
Width of sensor	40.5 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC

Utilisation category DC-13	4 A
Switching element	Normally open contact (NO)
Switching principle	Slow action with staggered contacts
Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Notes

Note (General) Switch with 2 NO contacts are not for security tasks

Ordering code

Product type description:

(1)(2) 3(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

1K Offset roller lever 1K

3K Angle roller lever 3K

RMS Brass roller

(3)

3 slim design

5 large design

(4)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

01/01 1 NC contact left / 1 NC contact right

12 1 NO contact/2 NC contacts

03 3 NC contact

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)

G24 with LED

(7)

without Cable entry M20

NPT Cable entry NPT 1/2"

ST M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

ST-2310 M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

(8)

2138 Roller lever 7H for position switches with safety function

(9)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: k335hf01


| 165,3 kB | .png | 74.083 x 197.556 mm - 210 x 560

Pixel - 72 dpi

| 524,1 kB | .jpg | 143.581 x 383.469 mm - 407 x 1087

Pixel - 72 dpi

Dimension/Product/Basic



ID: 1-335g01

| 105,8 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697


Pixel - 72 dpi

| 4,5 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

| 96,7 kB | .cdr |

Diagramm/Product/Travel

| 53,0 kB | .jpg | 352.778 x 115.711 mm - 1000 x 328
Pixel - 72 dpi
| 1,7 kB | .png | 74.083 x 24.342 mm - 210 x 69 Pixel -
72 dpi
| 18,6 kB | .cdr |



| 51,9 kB | .jpg | 352.778 x 135.819 mm - 1000 x 385
Pixel - 72 dpi

| 84,5 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701
Pixel - 72 dpi
| 65,6 kB | .cdr |
| 4,1 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi

+010001am31