

# XUB1APAWL2

photo-electric sensor - XUB - reflex - 90° - Sn  
4m - 12..24VDC - cable 2m



## Main

|                               |                                  |
|-------------------------------|----------------------------------|
| Range of product              | OsiSense XU                      |
| Series name                   | General purpose single mode      |
| Electronic sensor type        | Photo-electric sensor            |
| Sensor name                   | XUB                              |
| Sensor design                 | Cylindrical M18                  |
| Detection system              | Reflex                           |
| Material                      | Plastic                          |
| Line of sight type            | 90° lateral                      |
| Type of output signal         | Discrete                         |
| Supply circuit type           | DC                               |
| Wiring technique              | 3-wire                           |
| Discrete output type          | PNP                              |
| Discrete output function      | 1 NO                             |
| Electrical connection         | Cable                            |
| Cable length                  | 2 m                              |
| Product specific application  | -                                |
| Emission                      | Infrared reflex                  |
| [Sn] nominal sensing distance | 4 m reflex need reflector XUZC50 |

## Complementary

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| Enclosure material        | PBT                                               |
| Lens material             | PMMA                                              |
| Maximum sensing distance  | 5.5 m reflex                                      |
| Output type               | Solid state                                       |
| Add on output             | Without                                           |
| Wire insulation material  | PvR                                               |
| Status LED                | 1 LED (yellow) for output state                   |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection     |
| Supply voltage limits     | 10...36 V DC                                      |
| Switching capacity in mA  | <= 100 mA (overload and short-circuit protection) |
| Switching frequency       | <= 500 Hz                                         |
| Maximum voltage drop      | <1.5 V (closed state)                             |
| Current consumption       | 35 mA no-load                                     |
| Maximum delay first up    | 15 ms                                             |
| Maximum delay response    | 1 ms                                              |
| Maximum delay recovery    | 1 ms                                              |
| Setting-up                | Without sensitivity adjustment                    |
| Diameter                  | 18 mm                                             |
| Length                    | 62 mm                                             |






## Environment

|                                       |                                                                                                  |
|---------------------------------------|--------------------------------------------------------------------------------------------------|
| Product certifications                | UL<br>CE<br>CSA                                                                                  |
| Ambient air temperature for operation | -25...55 °C                                                                                      |
| Ambient air temperature for storage   | -40...70 °C                                                                                      |
| Vibration resistance                  | 7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6                        |
| Shock resistance                      | 30 gn (duration = 11 ms) conforming to IEC 60068-2-27                                            |
| IP degree of protection               | IP67 double insulation conforming to IEC 60529<br>IP65 double insulation conforming to IEC 60529 |

## Packing Units

|                  |          |
|------------------|----------|
| Package 1 Weight | 0.094 kg |
| Package 1 Height | 0.420 dm |
| Package 1 width  | 0.960 dm |
| Package 1 Length | 1.320 dm |

## Offer Sustainability

|                            |                                                                                                                                                                                    |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                              |
| REACH Regulation           |  <a href="#">REACH Declaration</a>                                                                |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                                                                                |
| RoHS exemption information |  <a href="#">Yes</a>                                                                             |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a>                                                  |
| Circularity Profile        |  <a href="#">End of Life Information</a>                                                        |


## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

Dimensions

---




---

## Wiring Schemes


---

### PNP Outputs



BN : Brown  
BU : Blue  
BK : Black

## Detection Curves



With reflector XUZY50