



BNS 120-12Z

- Ø M12
- Long life
- no mechanical wear
- Insensitive to soiling
- Thermoplastic enclosure
- Particularly large switching distance
- Insensitive to transverse misalignment
- Suitable for food processing industry only in combination with BP 15 SS

Data

Ordering data

	BNS 120-12Z
	101128297
EAN (European Article Number)	4030661050874
eCl@ss number, Version 9.0	27-27-24-02

Approval - Standards

TÜV
cULus
EAC

General data

	BNS 120
	IEC 60947-5-3
	BG-GS-ET-14
Installation conditions (mechanical)	quasi-flush
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	50 g

General data - Features

Coding	None
Number of openers	2
Number of shutters	1
Number of safety contacts	2
Number of cable wires	4

Safety appraisal

ISO 13849-1

Mission Time

20 Year(s)

Safety appraisal - Safety outputs

B10d- Value Normally-closed

contact/Normally open contact (NC/NO)

25,000,000 Operations

Mechanical data

Actuating element

Magnet

Ensured switch distance "ON" S_{ao}

20 mm

Ensured switch distance "OFF" S_{ar}

32 mm

Actuator switch distance

Actuating magnet BP 8, Sao: 10 mm

Actuating magnet BP 15 SS, Sao: 20 mm

Actuating magnet BP 10, Sao: 20 mm

Actuating magnet BP 6, Sao: 10 mm

Actuating magnet BP 8, Sar: 22 mm

Actuating magnet BP 15 SS, Sar: 32 mm

Actuating magnet BP 6, Sar: 22 mm

Actuating magnet BP 10, Sar: 32 mm

Direction of motion

Head-on to the active surface

Mechanical data - Connection technique

Terminal Connector

Cable

Length of cable

1 m

Wire cross-section

0.3 mm²

Wire cross-section

23 AWG

PVC

Mechanical data - Dimensions

Length of sensor

M12

38.5 mm

Ambient conditions

Ambient temperature, minimum

IP67

-25 °C

Ambient temperature, maximum

+70 °C

Storage and transport temperature,
minimum

-25 °C

Storage and transport temperature,
maximum

+70 °C

Resistance to vibrations to EN 60068-2-6

10 ... 55 Hz, amplitude 1 mm

30 g / 11 ms

Electrical data

Voltage type	AC (alternating current) DC (direct current)
Switching voltage, maximum	100 VAC
Switching voltage, maximum	100 VDC
Switching current, maximum	0.3 A
Switching capacity, maximum	5 W
Switching frequency, maximum	5 Hz

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

BP 10
BP 8
BP 6
BP 15 SS
SRB-E-301ST
SRB-E-201LC

Notes

	Contact symbols shown for the closed condition of the guard device.
Note (General)	The safety sensor must be mounted in such a way that actuation with another magnet is impossible (concealed mounting according to EN 1088)

Ordering code

Product type description:

BNS 120-(1)Z

(1)

11 1 NO contacts/1 NC contact

12 1 NO contact/2 NC contacts

02 2 NC contact

Pictures

Photo/Product/Catalogue

ID: kbns1f01

| 183,5 kB | .jpg | 104.069 x 382.058 mm - 295 x 1083
Pixel - 72 dpi

| 113,8 kB | .png | 74.083 x 271.639 mm - 210 x 770
Pixel - 72 dpi

Dimension/Product/Basic

ID: 1bns1g01

| 31,6 kB | .cdr |

| 5,1 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

| 63,8 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697
Pixel - 72 dpi

Graphic/Product/Contact

ID: k2o1sk05

| 43,5 kB | .jpg | 352.778 x 61.736 mm - 1000 x 175
Pixel - 72 dpi

Diagramm/Product/Curve

ID: kbns1a02

| 17,7 kB | .png | 74.083 x 46.567 mm - 210 x 132
Pixel - 72 dpi

| 133,7 kB | .jpg | 352.778 x 221.544 mm - 1000 x 628
Pixel - 72 dpi

| 137,1 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 162021-01-31T06:36:16+01:00601Europe/BerlinSun, 31 Jan 2021 06:36:16

+010016amSunday.31am31Europe/BerlinCET3601Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:36:16

+010001am31